

# County Surveyor's Record, Tillamook County, Oregon

PAGE 1

TOWNSHIP 5 SOUTH, RANGE 8 WEST

1/4 CORNER, SECTIONS 13/18, T5S, R9/8W

FOUND ORIGINAL 4 X 4 SQUARED, SCRIBED POST IN FENCE CORNER, FENCE RUNNING EAST AND NORTH. POST SCRIBED "1/4S" AND "GRIR".

SET 1 1/4" X 36" STAINLESS STEEL PIPE IN GROUND AT BASE OF POST.

FROM WHICH BEAR NEW B.T.'S. SCRIBED APPROXIMATELY 15 YEARS AGO (FACES GROWN OVER):  
20" FIR BEARS N 86°W 27.00 FT. U.S.F.S. YELLOW TAG  
19" FIR BEARS N 18°E 36.61 FT. ADDED YELLOW TAG

ALSO FOUND ROTTED-OUT STUMP WELL S 10°W 61 LINKS.

AUGUST 15, 1967

FOUND BY: W. BREWER, LFCO.  
WITNESS: R. BASS

C-W 1/16 CORNER, SECTION 18, T5S, R8W

FOUND ORIGINAL DEAD FIR B.T. BEARS N 50°E 28 LINKS, MARKED "1/8 S B.T."

SET 1 1/4" X 36 " STAINLESS STEEL PIPE.

BARK SCRIBED THE FOLLOWING NEW B.T.'S.:

28" ALDER BEARS N 43°W 18.60 FT. "C-W 1/16" S. NAIL, L. WASHER, Y. TAG  
22" ALDER BEARS S 59°W 10.73 FT. "C-W 1/16" S. NAIL, L. WASHER, Y. TAG

CORNER IS IN CREEK BOTTOM 15 FEET EAST OF CREEK AND IS ABOUT 300 FT. NORTH OF ROCK PIT ROAD.

AUGUST 17, 1967

SCRIBED BY: R. BASS, LFCO.  
WITNESS: W. BREWER

SECTION CORNER 18/17, T5S, R8W  
19/20

FOUND SW AND NW B.T. STUMPS:

40" FIR BEARS S 75°W 92 LINKS  
60" FIR BEARS N 55°W 88 LINKS

SET 1/2" IRON PIPE IN N-S FENCE.

SCRIBED THE FOLLOWING NEW B.T.'S.:

20" ALDER BEARS S 80°E 25.90 FT. BARK SCRIBED "S 20BT" S. NAIL, L. WASHER, Y. TAG  
40" FIR BEARS N 3°E 64.20 FT. "S 17BT" S. NAIL, L. WASHER, Y. TAG

CORNER IS 3 FT. SOUTH OF DRY CREEK, COURSE WEST.

AUGUST 29, 1967

SCRIBED BY: R. BASS, LFCO.  
WITNESSES: W. BREWER, R. MCCOLLAM

BOOK 3

BOOK 3

214