County Surveyor's Record, Tillamook County, Oregon

PAGE 7

TOWNSHIP I NORTH, RANGE 9 WEST

E 1/16 CORNER, SECTIONS 31, T2N, R9W

DROVE & IRON PIPE FOR CORNER; ESTABLISHED BY L.F.CO.

5

SCRIBED THE FOLLOWING:

40" FIR STUB 24 FT. HIGH BEARS N 78 E 15.4 FT. "E 1/16 S31" Y. TAG 31" FIR STUB 40 FT. HIGH BEARS S $20\frac{1}{2}$ E 54.6 FT. "E 1/16 S6" Y. TAG

CORNER IS 150 FT. WEST OF SADDLE AND 150 FT. SOUTH OF RIDGE TOP. ASPECT STEEP SOUTH. BARE HILLSIDE.

VAR. 21°30' JULY 18, 1962 SCRIBED BY: W. JORDAN. LFCo.

R. STEWART WI TNESS:

1/4 CORNER, SECTIONS 31, T2N, R9W 6 TIN R9W

SET 1 IRON PIPE FOR CORNER; RESTORED BY PROPORTIONATE MEASUREMENT BY L.F.CO.

REFERENCED THE FOLLOWING:

18" HEMLOCK BEARS N 42"W 10.3 FT. "4531" Y. TAG 6" SPRUCE BEARS \$ 66°W | 14.8 FT. "456"

CORNER IS 20 FT. EAST OF 40 FT. HIGH SHARP BLUFF, RUNNING N 20°E. CORNER IS EAST OF 6 FT. SPRUCE LOG AND 20 FT. NW OF ALDER DRAW.

VAR. 21° 301 SEPTEMBER 14, 1962 REFERENCED BY: W. JORDAN, LFCo.

WITNESS: R. STEWART

1/4 CORNER, SECTIONS 6/5, TIN, R9W

SET STAKE FOR CORNER; RESTORED BY PROPORTIONATE MEASUREMENT BY L.F. CO.

REFERENCED THE FOLLOWING:

10" FIR BEARS N 10"W 7.0 FT. "4 S6" Y. TAG 42" FIR STUMP BEARS \$ 68°E 10.7 FT. "4 \$5" Y. TAG

CORNER IS ON TOP OF ROCKY SPUR RIDGE, SLOPING EAST, ABOUT 350 FT. IN ELEVATION BELOW MAIN N-S RIDGE. ROCK FACE TO SOUTH AND DRAW TO NORTH.

CORNER IS 484 FT. N 7°09'W OF 300 FT. HIGH SHEER ROCK FACE.

VAR. 21° 30' JULY 17, 1962

REFERENCED BY: W. JORDAN, LFCO.

R. STEWART WITNESS:

N 1/16 CORNER, SECTIONS 6/5, TIN, R9W

DROVE 1 IRON PIPE FOR CORNER; ESTABLISHED BY L.F.CO.

5

SCRIBED THE FOLLOWING B.T.'S .:

Y. TAG 6" FIR BEARS N 54°E 39.5 FT. "N 1/16 85" 10" FIR BEARS N 25°W 34.6 FT. "N 1/16 86" Y. TAG

CORNER IS 30 FT. NORTH OF DRAW. SMALL SPUR RIDGE IS 40 FT. NORTH OF CORNER AND MAIN SPUR RIDGE IS ABOUT 80 FT. NORTH OF CORNER. CORNER IS 330 FT. EAST OF MAIN N-S RIDGE.

VAR. 21° 301 JULY 18, 1962

SCRIBED BY: W. JORDAN, LFCO.

WITNESS: R. STEWART

BOOK 3