Feet

1017.0 Approximate location, branch 6 feet wide course N 80 E

1239.0 Gravel road running east and west

1313.9 Point for the CS 1/16th corner. Set in ground an iron post 2" x 30" with brass cap marked

T 5 S R 10 W

S 21

CS 1/16

1968

ORLS 650

from which

- A hemlock 8 inches in diameter bears N 37 3/4 W 5.4 feet Scribed CS 1/16 S 21 BT 650
- A hemlock 6 inches in diameter bears S 19½ W 6.3 feet Scribed CS 1/16 S 21 BT 650

Continuing N 0-40-14 W

1552.9 Enter Timber

2627.8 Center ½ corner, found scribed 4" x 4" x 48" wooden post, as set by Carlich, for the corner

from which

A spruce stump 42 inches in diameter bears N 38 E 18.7 feet

A hemlock 22 inches in diameter bears S 49 W 11.0 feet

At the corner point set in the ground an iron post 2" \times 30" with brass cap marked

T 5 S R 10 W

\$ 21

C 1/4

1968

ORLS 650

REGISTERED OREGON LAND SURVEYOR

JULY 10, 1964 TOM O. MCCULLOUGH

650

from which a new bearing tree:

A hemlock 38 inches in diameter bears S 81 3/4 E 35.5 feet Scribed C ½ S 21 BT 650

Deposited wooden post alongside iron post.

Continuing north along transit random line describing true line which bears N 0-18-14 W