Cou Surveyor's Record, Tillamook Cov Oregon

RESTORED CORNER FOR STATE OF OREGON-DEPARTMENT OF FORESTRY

One-Quarter corner common to Sections 23 and 24, Town-ship 2 North, Range 10 West, Willamette Meridian,

CHAINS

ORIGINAL

Tillawook County, Oregon.

Post (missing, found 14" iron pipe in place) from which a:

10th Alder bears N 60 W 5 lks.; missing.
10th Hemlock bears S 60 E 5 lks.; missing.
Very old rail fence runs West and South from pipe.

See affidavit dated June 6, 1968. Fence described in affidavit has since been destroyed.

REWITNESSED

Var. 21 E

Set $1\frac{1}{2}$ " x 36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF FORESTRY 1/4 S23 S24 1968 RS 707", in place of above $1\frac{1}{4}$ " iron pipe, and from which a:

42" Hemlock bears N $69\frac{1}{2}$ W 41.5 ft.; scribed 1/4 S23 BT. 33" Hemlock bears S 54 E 16.2 ft.; scribed 1/4 S24 BT RS 707.

Set 4" x 4" x 48" white painted Cedar post 1.0 ft. NE of corner pipe. Oregon State Forestry Department metal location poster on 33" Hemlock BT.

Dated July 29, 1968.

Restored by

Arved Russell
HAROLD J. RUSSELL

Present and witnessed by C. Curl
Asberry Miner

Le reverse side of sheet.

BOOK 3

RESTORED CORNER FOR STATE OF OREGON-DEPARTMENT OF FORESTRY

CHAINS

Witness Point (Line Tree) common to Sections 4 and 9, Township 3 South, Range 8 West, Willamette Meridian, Tillamook County, Oregon.

ORIGINAL

34" Fir line tree at 4.08 chains West of the 1/4 corner common to Sections 4 and 9 (now 72" snag 18' tall, 3 notches on West 3 notches on East sides).

WITNESSED

Var 21\frac{1}{2}^0 E

26" Fir bears S 43 W 26.2 ft.; scribed W P S9 BT RS 707. 19" Fir bears N 7 W 31.3 ft.; scribed W P St BT.

One quarter corner common to Sections 4 and 9 bears N 85° 20' 54" E 213.3 ft.

Oregon State Forestry Department metal location poster on 19" Fir BT.

Dated July 24, 1968

Restored by

Present and witnessed by C. Curl

G. Lankow

HAROLD J. RUSSELL

W. Coblentz