


CERTIFIED RECORD OF LAND CORNER MONUMENTAL

History of original corner establishment:

Sam Caudle set corner in 1880. In 1887 Tillamook County Surveyor scribed a snag. M. Whitmore found snag in 1955, scribed 2 new BTs and set a post and a pipe.



Caudle set a post from which
A 24" fir brs. S68W 10 lks

Tillamook County Surveyor set a post from which
A 48" snag brs. N74E 160 lks

← see Book 1 Page 21
JK

Description of corner evidence found:

Found 3/4" pipe and a 2"x4" post with 1/4 S29 on west side
and S28 on east side (Whitmore, 1955) from which

A 48" snag brs. N74E 105.6 ft
scribing visible (Tillamook Co. Surveyor, 1887)

A 27" fir brs. N81E 28.7 ft
face healed (Whitmore, 1955) ← see Book 1 Page 241
JK

A 29" spruce brs. N53W 15.5 ft
face healed (Whitmore, 1955)

Description of monument and accessories I established to perpetuate the original location of this corner

Set 2"x30" iron pipe with brass cap mkd

T5S R9W

1/4 29 | 28
1970
650

Reset 3/4" pipe and scribed post beside brass cap why?

Drove a steel fence post + 5 ft west of corner facing south with F.S. boundary and attention signs attached.
Steel fence post + 5 ft south of corner facing west with F.S. boundary sign attached. Painted red band on BTs. Placed BT sign on snag.

Office of COUNTY SURVEYOR County of TILLAMOOK
State of OREGON, I hereby certify that the within instrument was filed in this office
for record on the 8th day of JULY, 1970, at 6 o'clock PM, (signed)
[Signature] by [Signature]
(COUNTY OFFICIAL) (DEPUTY)

REGISTERED
OREGON
LAND SURVEYOR

[Signature]
JULY 10, 1964
TOM O. McCULLOUGH
650