CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was originally established by William Wright in 1882. He came South from the corner to Sections 29, 30, 31, and 32, 40 chains and marked:

"A Hemlock, 6 ins. diam., for & Sec. Gorner, mkd. &S on West face; from which Hemlock, 7ins. diam., bears N.10°E., 32 links dist., mkd. & S BT.

Hemlock, 9ins. diam., bears S.47°E., 28 links dist., mkd. & S BT."

DIAGRAM T.5S., R.9W. ½ \$31/\$32

At that point he states the land to be rough and broken and does not continue on and tie to the corner to Sections 31, 32, 5, and 6.

(Contract Survey)

Description of corner evidence found:

I could find no evidence of the original corner or its accessories. I did find an $1\frac{1}{4}$ " Iron pipe 2 feet above ground set by John Cdrlich in 1955. This pipe was set by single proportionate measurement between the two section corners.

Description of manument and accessories I established to perpetuate the original location of this corner

I set a 2"x36" Iron pipe with a flared bottom and brasscap riveted to the top marked: T.55., R.10W.

\$31/\$32 1971 0.L.S. 816

Per Manual instruction at a distance of 2640 feet South (Solar observation), from the corner common to sections 29, 30, 31, and 32.

I scribed the following BT's and placed tags and painted red bands on them

17" Hemlock N.49°E. 752 ft., mkd. "\2832BT"
42" Spruce Stump S.49°W. 97 ft., mkd, "\2831BT"
1\2818TT Top pipe \$879-341, 4500.

1½"Iron pipe \$87°-34'-45"W. 426.54 feet (Carlich 1955)

I erected a small stone mound around the brasscap and set a 6 foot steel post with and "Attention" sign 2 feet West.

Witnessed:

M. Yinger

Set this 21st day of September 1971

800K 5

Kennett M. Wight

NOLY 17, 1970

KENNETH M. WIGHTMAN II

LAND

189