CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner has never been established.

DIAGRAM J

1/256 CSNNW

Section 6

Reference:

Plat dated July 1973 by Timberland Services, Inc. under my stamp.

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2 1/2" X 30" galvanized iron pipe with a flared bottom and a brasscap riveted to the top marked: $$\rm T$ 6 S $\,\rm R$ 10 W

S 6

CSNNW

1/256

.

RLS 942

By proportional measurement. From which a:

12" Alder S 1° W 250.1 ft mkd "CSNNW 1/256 S 6 BT" 14" Hemlock N 30° E 85.5 ft.

mkd "CSNNW 1/256 S 6 BT"

Witnessed: E. R. Cook

Office of County Surveyor County of TULAMOUL

State of OPEGOD I hereby certify that the within instrument was filed in this office
forecord of the 20 day of August , 1973, at 920 o'clock A.m., (signed)

by

Set this 19th day of July 1973.

BOOK 5 Edgar R Cook

238

(DEPUTY)

TIMBERLAND SERVICES, INC. P.O. Box 668 - Albany, Ore. 97321 Phone: 928-3539 REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON JULY 17, 1970 KENNETH M. WIGHTMAN II 942

Form R6-7100-57 (9/66)