

County Surveyor's Record, Tillamook County, Oregon

6

Feet Following is the description of the true township line and all pertinent corners, restored, reestablished, and established:

Beginning at the corner to T3 and 4S, R9 and 10W, W. M., which is an Oregon State Department of Forestry iron post with brass cap marked

R10W	R9W
36	31
T3S	
1	6
T4S	

from which

- A 32" Hemlock stub bears (S43°W, 203.5 feet)
- A 16" Hemlock bears (S39½°W, 258 lks)
- A 14" Fir bears (N89¼°W, 214.5 feet)
- A 5" Fir bears (N17°E, 238 lks)
- This is an original BT--now a decayed stump.
- A 19" Fir bears (N50°E, 140.2 feet)
- A 18" Fir bears (S48½°E, 252.4 feet)

S88°34'42"E,

between T3 and 4S, R9W

- 632 power line bears north-south
- 742 spur bears north-south, descend
- 998 branch, course northwest

1234.93 position for the W 1/16 to Section 6, T4S, R9W, I set a 2½" x 30" iron post with brass cap marked

T3S	R9W
31	W 1/16
6	
1974	650

from which

- A 24" Fir bears S70°E, 32.8 feet
scribed W 1/16 S6 BT.
- A 16" Alder bears S2°E, 34.9 feet
scribed W 1/16 S6 BT.

continuing on same bearing

2866.12 the south 1/4 corner to Section 31 as established by Henry Meldrum and remonumented by Samuel Caudle. Found an iron pipe at position of corner (no evidence of Caudle's stone). I set a 2½" x 30" iron post with brass cap marked

T3S	R9W
31	
6	
1974	650

See map B-661