CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

This corner was originally set the the G.L.O. in 1880 under Contract No. 364. They set a post and marked two BT's.

> 4" Vinemaple N 76° W 5 lks.

4" Vinemaple S 30° E 30 lks.

DIAGRAM T5S R9W 1/4 S 5 | S 4

Description of corner evidence found:

I found no evidence of the original corner or its accessories. In 1895 the County Surveyor set a post and marked 2 BT's.

8" Crabapple S 85° E 134 1ks.

6" Maple S 29° W ll6 lks.

This corner was found and a pipe was set in 1924 (A-181). No mention was made as to the method in which this corner was set and it is evident that he came south 40 chains from 32 33 . This pipe was plowed out and another set in its approximate 5 4

position by Mr. Claus Erickson. I found this later pipe. CS A-1605 uses this pipe for control.

Description of monument and accessories I established to perpetuate the original location of this corner

After consultation with the G.L.O., I disclaim this 2" pipe as a valid corner. At proportionate measurement, I set a 2 1/2" x 30" galvanized iron pipe with a brasscap riveted to the top marked:

> T5S R9W S 5 4 S 4 1975

> > RPLS 942

from which:

27" Maple N 39° E 94.9 feet mkd. "1/4 S 4 BT"

2" pipe (CS A-1605) S 64° 08' 45" E 210.01 feet

All bearing trees have been banded with red paint and attention signs and BT tags have been attached. All scribes have a 3/4" brass washer, with "LS 942 engraved on it, nailed in the face.

Witnessed: E. W. Tatro

..... County of for record on the day of (COUNTY OFFICIAL) by (DEPUTY)

Set this 31st day of January 1975

Monte A. Cook Forest Technician

Monte a Cook

318

LAND SURVEYING - ENGINEERING LAND USE PLANNING - ROADS FORESTRY CONSULTING

OREGON KENNETH M. WIGHTMAN II 942

REGISTERED

PROFESSIONAL

LAND SURVEYOR

Form R6-7100-57 (9/71)

BOOK 5



± GPO 796-333