County Surveyor's Record, Tillamook County, Oregon

PAGE 7

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment: Corner established by Samuel ... Snowden in 1857 under G.L.O. Contract No. 67. Snowden

Survey A-607 that he found a 2 inch iron pipe and the origi-

nal scribed spruce limb at this corner. At present I have not found any evidence as to who set the 2 inch iron pipe, but the finding of said pipe, and/or original scribed spruce post is also reported on county surveys B-472, B-155, A-540, And F-22-14.

CORNER DIAGRAM

7º 25

R9W

Description of corner evidence found:

I found the 2 inch iron pipe reported by Carlich in Sept. 1950. I also found the top of the original spruce post lying along side of said pipe. Scribing is visible. From said iron pipe I found the following two bearing trees scribed by Carlich: 20 inch hemlock bears N 50° E 10.1 ft. to old scribed face. 26 "hemlock bears S 39° W 18.3 ft. to old scribed face on root collar. No trace of original bearing trees.


Description of monument and accessories I established to perpetuate the original location of this corner:

I removed the 2 inch iron pipe and in its place set flush a 2" X 36" concrete filled, galv. iron pipe with a 3 inch brass cap stamped as shown,

from which I scribed two bearing trees:

24 in. hem. bears N 54° W 25.5' to face scribed " 1/4S7BT".

26 in. hem. bears S 68° E 34.2 ' to face scribed " 1/4S18BT ".



REGISTERED PROFESSIONAL LAND SURVEYOR

> · old OREGON JULY 12 1368 KARL F FOESTE

VILUMASSES. TRINITE SERVICE	*****	
Recorded in the office of Surveyor	County of	Tillamook
State Orașon , I hereby o	ertify that the within instrument	was filed in this office
by		
BOOK 5 (county official)	(deputy)	

KARL F. FOESTE, Registered Professional Land Surveyor of the State of Oregon

346 BOOK