CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by Samuel D. Snowden in 1856 under G. L. O. Contract No. 67. Snowden reports: "Set post for corner to Sections 34, 35, 3, and 2, from which; A Hemlock 16 ins. diam. bears N 53° W 44 lks. dist. A Hemlock 16 ins. diam. bears N 38° E 32 lks. dist. A Hemlock 12 ins. diam. bears S 13° E 75 lks. dist. A Hemlock 40 ins. diam. bears S 30° W 34 lks. dist.

CORNER DIAGRAM

T2S, RIOW, W.M.

S34 | 535 |

53 |

T35

In County Survey Book 3, Page 302, C. G. Collard reports: 0
"On May 8, 1969, I found the 16" Hemlock, bearing N 53° W (now a rotting stump) with incomplete scribe marks visible. The 16" Hemlock bearing N 38° E and 40" Hemlock (also rotting stumps) are properly located in relation to the corner, but no face or marks are found. From these original bearing trees I set a 3/4 iron pipe with 3 inch brass cap for the corner to Sections 34 and 35, T2S, R10W, on the Townshiplline between T2S and T3S, R10W, W.M. I marked new bearing trees as follows: 14" Hemlock bearing N44° E 52.1 feet, scribed "BT-S35-T2S". 12" Spruce bearing N 43° W 14.8 feet, scribed "BT-S34_376" 10" Spruce bearing S 46° W 14.3 feet, scribed "BT-S3-T3S,R10W".

Description of corner evidence found:

I found the 3/4 inch iron pipe with 3 inch brass cap set by Collard in May 1969, from which I found all three of collards new bearing trees to bear as reborted by him in County Survey Book 3, Page 302. I also found the remains of all four of the original bearing trees set by Snowden in 1856. From Collard's corner the estimated face position of the original B. T.'s bear as follows: 30" Hem. Stump brs. N 41° E 21.0 ft. 20" Hem. stump brs. N 52° W 29.5 ft. 50" Hem. stump brs. S 24° W 20.1 ft. Fallen 12" Hem. snag brs. S 15° E 49 ft. to re-constructed upright position, original scribing "BT" is plainly visible.

5-736

Description of monument and accessories I established to perpetuate the original location of this corner:

I, Karl F. Foeste, hereby certify that I witnessed the above corner as herein described in October, 1976.

Witnesses:

Harold a. Engslerg allen F. Hofmann REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
JULY 12, 1968
KARL F. FOESTE
0849

Recorded in the office of Surveyor , County of Tillamook

Oregon , I hereby certify that the within instrument was filed in this office

for record on the 15 nd day of Manday 1976

(county official) by

(deputy)

KARL F. FOESTE, Registered Professional Land Surveyor of the State of Oregon

Buch 6