## CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Wilson in 1890 set a post 4" sq., 4 ft. long, 24" deep, mkd. 4 S on N. face from which:

Hemlock 24" diam. bears S  $77\frac{1}{20}^{0}$ W, 57 lks. mkd.  $\frac{1}{4}$  S BT Hemlock 24" diam. bears N  $77\frac{1}{2}^{0}$ E, 56 lks. mkd.  $\frac{1}{4}$  S BT

DIAGRAM T 6 S R 10 W <u>S</u> 12

Description of corner evidence found:

Monument found:

 $\frac{1}{2}$ " x 48" iron rod and  $\frac{1}{2}$ " x 53" GIP tipped over,  $\frac{1}{2}$ " GIP set by J. S. Forrest, Deputy County Surveyor in 1950 who saw orig. scribing on NE BT. Iron rod set by L. Whitmore

Also found in center of hole 2" sq., 8" long sharpened post 6" below surface, believed to be the remains of Wilson's orig. post. This taken to Supervisor's Office in Corvallis, OR.

BT's found:

Hemlock 12" diam. bears N 190W 8.5 healed blaze and Fir 12" diam. bears S 83 E 19.6 ft.

healed blaze established by L. Whitmore in 1973.

Hemlock stump 24" bears S 77 ½ W 57 lks. (orig. BT) no marks visible.

Hemlock windfall 40" diam. bears N 77 ½ E. 56 lks (orig. BT) no marks visible.

Hemlock stump 40" diam. bears S 160W, 70.3 ft., no marks visible possible face, (Forrest's BT).

Hemlock stump 40" diam, bears S 160W, 70.3 ft., no marks visible possible face, (Forrest's BT).

Description of monument and accessories pestablished to perpetuate file. (Forrest's BT).

original location of this corner: September 10, 1979

Set an aluminum post (with magnet in top and bottom) 30" long, 3" diam., 24" in the

ground, with aluminum cap mkd.

1/2" rod and 1/2" GIP buried alongside aluminum post.

T 6 S R 10 W

S 12 5 13

LS 1017

1979

Accessories:

No additional bearing trees required. Painted 6" red band on BT's. ATTN sign on back of all stumps and trees. Placed ATTN sign on post 5'± west.

Basis of Bearing Staff compass was used with a declination of 21°E. I certify this remonumentation and record thereof, was prepared by me or my assistants under my supervisory direction and is true and correct to the best of my knowledge.

Witness

Witness \_

Duane Garoutte

Witness

Richard Chesebro

REGISTERED PROFESSIONAL LAND SURVEYOR

GORDON H. LONG

Office of County Surveyor County of Tillamook State of....Oregon......, I hereby certify that the within instrument was filed in this office County Surveyor J. L. Carlich by Allan E Duncan (COUNTY OFFICIAL)

Form R6-7100-57 (9/71)

☆ GPO---798-276