Remonumentation of Certain Original Corner Points, T. 4 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A fir, 19 ins. diam., bears S. 30½° W., 60 1ks. dist., mkd. ¼ S16 BT.

Deposit corner stone and set a 5 ft. steel fence post alongside iron post.

The ½ sec. cor. of secs. 3 and 4, perpetuated and recorded by Mervin Whitmore, Deputy County Surveyor, in 1953, monumented with a fir post, 5 ins. square, lying on the ground, from which the remains of the original bearing trees:

A sawed fir stump, 40 ins. diam., bears S. 23½° E., 49 lks. dist., with fragmentary scribe marks visible on open blaze.

and bearing trees mkd. by Whitmore

A fir, 13 ins. diam., bears S. 73° E., 4 lks. dist., with healed blaze.

A fir, 14 ins. diam., bears N. 59° W., 32 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 9 W

5 4 S 3

1978

Reset fir post and set a 5 ft. steel fence post alongside iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 16 and 21, perpetuated and recorded by Leonard Whitmore, Deputy County Surveyor, in 1961, monumented with the original basalt stone, 12 x 10 x 10 ins., firmly set, 8 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, mkd. with  $\frac{1}{4}$  S16 on N. and  $\frac{1}{4}$  S21 on S. faces, from which the remains of the original bearing trees:

A sawed fir stump, 38 ins. diam., bears N. 48½° E., 281 lks. dist., with fragmentary scribe marks visible on opened blaze.

and the remains of bearing trees mkd. by Whitmore

A sawed fir stump, 14 ins. diam., bears S. 6½° W., 121½ 1ks. dist., with scribe marks ½ S21 visible on open blaze.

At the corner point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 9 W

1/4 S 16/S 21

1978

112

**BOOK 6**