Remonumentation of Certain Original Corner Points, T. 4 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 4 S R 9 W

1/4 S 2 S 11

1978

Reset fir post and set a 5 ft. aluminum fence post alongside iron post.

The ½ sec. cor. of secs. 21 and 22, perpetuated and recorded by Mervin Whitmore, Deputy County Surveyor, in 1961, monumented with the original fir post, 3 ins. square, 30 ins. long, firmly set 6 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, with scribe marks S on E. and S21 on W. faces, from which the remains of the original bearing trees:

A decayed fir snag, size indeterminate, bears N. 43° E., 30 lks. dist., with scribe mark 4 visible on open blaze.

and bearing trees mkd. by Whitmore

- A fir, 18 ins. diam., bears N. 79° E., $20\frac{1}{2}$ 1ks. dist., with healed blaze.
- A fir, 15 ins. diam., bears S. 85° W., 5 1ks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 4 S R 9 W

5 21 | S 22

1978

Reset fir post and set a 5 ft. steel fence post alongside iron post.

The cor. of secs. 15, 16, 21, and 22, perpetuated and recorded by John Carlich, Registered Land Surveyor No. 287, in 1953, monumented with the original cedar post, 4×6 ins., loosely set, projecting 20 ins. above ground, and in a mound of stone, 2 ft. base, 1 ft. high, with scribe marks S22 on SE. and S on SW. faces, from which the remains of the original bearing trees:

- A decayed fir snag, size indeterminate, bears S. 29° E., 115 lks. dist., with scribe marks BT visible on open blaze.
- A decayed cedar snag, size indeterminate, bears N. 56½° W., 167 lks. dist., no marks visible.

and bearing trees mkd. by Carlich

A fir, 19 ins. diam., bears N. 68° E., 26 lks. dist., with healed double blaze.

114

BOOK 6