REWITNESSED CORNER FOR STATE OF OREGON--DEPARTMENT OF FORESTRY

Township corner common to Sections 1, 6, 31, and 36, T2 & 3S, R6 & 7W, W.M., Tillamook County, Oregon.

ORIGINAL

Stone 24"x12"x10" (now at base of pipe, no marks visible). Did not mark any bearing trees.

WITNESSED by Albert P. Wilson, June 16, 1891

From above stone, 12x10x6 marked with 6 notches in N & E faces from which a:

- 50" Fir bears N52½ W 12 lks.; now 46" stump, 8 ft. high with axe work and portions of scribes visible.
 - 4" Vine maple bears S41° E 12 lks.; missing.

RESTORATION by U.S. Cadastral Surveyor number 191 3"x36" galvanized iron pipe with $3\frac{1}{2}"$ cap, original stone deposited at base (pipe in place, no marks on stone visible) from which a:

56" Fir stump bears N52°W 12 lks., now 46" stump, with T2SR7W S36 BT visible (along side remains of 1891 face).

Mound of stone, 6 ft. base, 3½ ft high south of corner; now S40°W 3 ft. to center.

REWITNESSED

Var. 20⅓°E

From above cadastral pipe and cap marked "T2S, R7W, R6W, S36 S31 S1 S6 T3S 1940 191," added 1980 RS707,28 inches in ground, in mound of rock, and from which a:

- 19" Fir bears S06°W 41.5 ft. to face; scribed T3SR7W S1 BT RS707.
- 16" Fir bears S47°E 19.5 ft. to face; scribed T3SR6W S6 BT.
- 11" Fir bears N172°E 47.8 ft. to face; scribed T2SR6W S31 BT.
- 9" Fir bears N85°W 107.0 ft. to face; scribed T2SR7W S36 BT.

Set 4"x4"x60" white painted Cedar post SW 1.0 ft. from corner pipe. Oregon State Forestry Department metal location poster on 16" Fir BT. Also poster on 56" Fir stump BT.

Dated November 25, 1980

Rewitnessed by Buchholz, Ass't Distirct Engineer

Present and witnessed by Danny Bensen Dave Wells

REGISTERED **PROFESSIONAL** AND SURVEYOR

ORE∉ON JULY 1965 HAROLD J. RUSSELL 707

1(mn