County Surveyor's Record, Tillamook County, Oregon

CHAINS	
	RESTORED CORNER FOR STATE OF OREGONDEPARTMENT OF FORESTRY
Section of Oregon.	corner common to Sections 16, 17, 20, and 21, T2N, R8W, W.M., Tillamook County
PRIGINAL	
14" X 9" which a:	X 7" stone; missing, found 4" X 4" X 84" Cedar post in mound of stone from
12" Hemlo 8" Hemloc scribes v	ck bears N70°E 43 lks.; now 15" badly rotted stump, scribes WS16 visible. k bears S60°E 15 lks.; now 17" uproot, found axe work and cruisers marks, no isible.
14" Hemlo scribes v	ck bears S52°W 10 1ks.; now 20" uproot, found axe work, face burned dut. no
	ED by Louis W. Amort, December 14, 1954.
	ound of rock around above stone, (in place) from which a:
p4" Hemio	tump bears N58°W 65.6 ft.; now 66" stump, scribes T2NR8WS17BTRE2311 visible. ck stump bears S03½°W 96.5 ft.; now 54" stump, face rotted, scribes T2NR8WS20B
Aizible.	ck snag bears Sll½°E ll.3 ft.; now 60" stump, face rotted, scribes T2NR8WS21
- Øregon Sta	ate Board of Forestry metal location poster on 24" Hemlock snag 135 ft. N55°E edge of logging road; now 24" stump poster missing.
RESTORED	Var. 21½°E
Set 7½" X FORESTRY	36" galvanized iron pipe with 3" bronze cap marked "OREGON STATE BOARD OF CONREWS17,S16,S20,S21 1981 RS1662", in mound of rock, and from which a:
9" Hemlock	Fir bears N45°W 13.1 ft. to face; scribed T2NR8WS17BTRS1662. Fir bears N55°E 11.2 ft. to face; scribed T2NR8WS16BT. bears S24°E 9.3 ft. to face; scribed T2NR8WS21BT. Fir bears S24°W 13.8 ft. to face; scribed T2NR8WS20BT.
Set 4" X 4 Forestry E stump BT.	X 84" white painted Cedar post SE 1.5 ft. from corner pipe. Oregon State epartment metal location poster on 9" Hemlock BT. Also poster on 66" Fir
Dated Sept	ember 8, 1981.
Restored b	y David B. Buckley under my direction.
	David B. Buchholz, Transitman REGISTERED PROFESSIONAL LAND SURVEYOR
	OREGON JULY 14, 1978 LOREN R. STEELE 1662
Present and	witnessed by <u>Danny Benson</u> .