CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

In 1898, Charles Branson subdivided T4S R9W WM under Contract #687. At the sec. corner 5/4, he set an alder post 5' long 8 9 4" sq., 24" in the ground, marked T4S S4 on NE, R9W S9 on SE, S8 on SW, S5 on NW, with 5 notches on the South and four on the East from which;

DIAGRAM **T4S R9W** 5 4 8 9

an alder 4" diam bears N73°E 29 1ks (19.1') marked T4S R9W S4BT

an alder 6" diam bears S69 1/4°E 26 1ks (17.2') marked T4S R9W S9BT

an alder 5" diam bears S84 1/2°W 30 1/2 1ks (20.1') marked T4S R9W S8BT

an alder 8" diam bears N33°W 36 1ks (23.8') marked T4S R9W S5BT

Description of corner evidence found:

Monument found-none

BT's found:

an alder 13" diam bears N73°E 18.4' (record 19.1) healed face-opened up-rotten face, no marks found.

an alder 20" diam bears S69 1/4°E 17.2' healed face

an alder 23" diam bears S87°W 19.2' (Record 20.1) healed face.


an alder 25" diam bears N33°W 23.8' healed face

Description of monument and accessories I established to perpetuate the original location of this corner:

At a mean position of Record Bearing and distances, I set 1/2"x5' piece of rebar with aluminum cap attached, marked T4S R9W

Set fiberglas post & decal 3' North.

S5 S4 S8 S9 RLS 1886 19 83



Accessories set: an alder 22" diam bears N80°E 22.9 marked T4S R9W S4BT. Bark scribed.

a fir 46" diam bears $$13^{\circ}$E 48.3$ marked T4S R9W S9BT on a single blaze

a 2 1/2" brass cap on a 30" galvanized iron pipe marked T4S R9W 7 38 ₽ cap approx. 8" out of ground. Bears S43°W 38.0'

Set fiberglas post & decal 3' North.

All distances measured to aluminum nail in side of tree. All BT's have red band and attn sign on back New BT's have brass washer.

S8 RM RLS 1886

S8 RM RLS 1886

38≗

T4S R9W

Equipment used: Kesson tape

loggers tape clinometer

staff compass (Var 21°)

CREW:

Chesebro

Hunnemuller Johnson, F.

Date: 1/19/83

REGISTERED **PROFESSIONAL** LAND SURVEYOR ray a Chan OREGON

RICHARD A. CHESEBRO

Office of County Surveyor County of Tillamook

State of Oregon , I hereby certify that the within instrument was filed in this office

for record on the...3... day of. February , 19.83 allan & Duncan, C.S. by

(COUNTY OFFICIAL)

Form R6-7100-57 (9/71)

☆ GPO---798-276