RESTORED CORNER FOR STATE OF OREGON--DEPARTMENT OF FORESTRY

Line tree (common to) Sections 20 and 29, T3N, R7W, W.M., Tillamook County, Oregon.

ORIGINAL

60" Fir line tree; now a 60" stump with no marks visible.

1.71 chains West top of spur; Crs. N60^OE; in place.
Section Corner 20,21,28 & 29 bears East 1.29 chains, from which
top of spur sloping NE bears North 3 chains; in place.

RESTORED

VAR 21½°E

Set 5/8"x30" iron rod with yellow plastic cap marked P.L.S. 1662, 20" in center of 60" line tree stump, and from which a:

8" Fir bears N83 $3/4^{\circ}W$ 28.6 ft. to face; scribed WP S20 BT. 40" Fir bears S35 $^{\circ}W$ 48.27 ft. to face; scribed WP S29 BT.

Set 4"x4"x60" white painted Cedar post NE 1.0 ft. from iron rod. Oregon State Forestry Department metal location poster on 8" Fir BT.

Dated: August 13, 1985

Restored by:

PROFESSIONAL LAND SURVEYOR

> OREGON JULY 14, 1978 LOREN R. STEELE 1662

Present and witnessed by: S. Ellis
O. Hendrick