


## TILLAMOOK COUNTY SURVEYORS OFFICE TILLAMOOK COUNTY COURT HOUSE 201 LAUREL AVENUE TILLAMOOK, OREGON 97141

# 1/4 CORNER COMMON SECTIONS 15 & 22 T.3N.,R.8W.,W.M.



I SET A 1 1/2" IRON PIPE WITH A 3" T.C.S. BRASS CAP IN A 10" CONCRETE CYLINDER, FROM REMAINS OF ORIGINAL BEARING TREES AS SHOWN IN HISTORICAL PARAGRAPH BELOW.

### HISTORY OF FOUND MONUMENT

THIS CORNER WAS RESET FROM ORIGINAL EVIDENCE COMPILED FROM FIELD INVEST-GATION OF SIGHT. ORIGINAL EVIDENCE, INCLUDING TOPOGRAPHICAL SUPPORT, LISTED BELOW AS FOLLOWS:

(ORIGINAL) 48" HEMLOCK S75"W 48 LINKS; (FOUND, REMAINS OF HOLLOW ROOT CROWN AT POSITION. THE SIZE OF ROOT CROWN IS CONSISTENT WITH THE SIZE OF THE ORIGINAL 48" BEARING TREE).

(ORIGINAL) 20" HEMLOCK N53°30'W 59 LINKS; (FOUND, ROTTEN HEMLOCK STUB 3' HIGH. JUDGING FROM ROTTEN REMAINS, APPEARS TO BE OF SUFFICIENT SIZE TO SUPPORT ORIGINAL 20" CALL).

(ORIGINAL TOPO CALL) 38.5 CHAINS FOOT OF STEEP DESCENT, 1.15 CHAINS N89°32'E OF THE 1/4 CORNER; (FOUND, AT POSITION).

(ORIGINAL TOPO CALL) 44.00 CHAINS TRAIL BEARS NORTH & SOUTH, 4.35 CHAINS \$89'32'W OF THE 1/4 CORNER; (FALLS IN A FLAT AREA, A VERY LIKELY POSITION FOR A TRAIL).

(ORIGINAL TOPO CALL) 56.00 CHAINS BROOK 4 LINKS WIDE RUNS NORTH ASCEND FROM BROOK 75 FEET, 16.35 CHAINS S89'32'W OF THE 1/4 CORNER; (FOUND, A BROOK AT THE TOE OF A STEEP SLOPE  $\pm$  15 CHAINS WEST OF THE 1/4 CORNER).

### **NEW ACCESSORY**

- \*16" DOUBLE HEMLOCK S20"W 65.28' SCRIBED 1/4 S22 CS BT. THE DISTANCE WAS MEASURED TO A NAIL WITH A BRASS T.C.S. WASHER NAILED TO THE FACE BETWEEN THE "B" AND THE "T".
- \*26" FIR N42"E 61.68' SCRIBED 1/4 S15 CS BT. THE DISTANCE WAS MEASURED TO A NAIL WITH A BRASS T.C.S. WASHER NAILED TO THE FACE BETWEEN THE "B" AND THE "T".
- \*10" ALDER S77E 9.19' SCRIBED 1/4 S22 CS BT. THE DISTANCE WAS MEASURED TO A NAIL WITH A BRASS T.C.S. WASHER NAILED TO THE FACE BETWEEN THE "B" AND THE "T".
- \*15" ALDER N 6"W 43.67' SCRIBED 1/4 S15 CS BT. THE DISTANCE WAS MEASURED TO A NAIL WITH A BRASS T.C.S. WASHER NAILED TO THE FACE BETWEEN THE "B" AND THE "T".
- \*72" HAT SECTION POST NORTH 1.5'.
- \*INDICATES TILLAMOOK COUNTY SURVEYORS YELLOW METAL LOCATION POSTER ATTACHED.

### SURVEYS AND REWITNESSES OF RECORD

SEE GENERAL LAND OFFICE MICROFILM 3N8 FOR THE ONLY RECORD OF THIS CORNER.

# LOCATION OF MONUMENT

THIS CORNER IS LOCATED APPROXIMATELY 0.7 MILE NORTHERLY ALONG BUCK MOUNTAIN ROAD FROM THE INTERSECTION OF SIBLEY CREEK ROAD AND 800' EAST OF BUCK MOUNTAIN ROAD IN A FLAT AREA BETWEEN RIDGES.

IN THE PRESENCE OF AL DVORAK AND DAN MCNUTT

JANUARY 25, 1995

TITLE:

PROFESSIONAL LAND SURVEYOR

OREGON JULY 14, 1967 ALLAN E. DUNCAN 793

RENEWAL DATE 12-31-95