
CERTIFIED RECORD OF LAND CORNER MONUMENATION

History of original corner establishment:

In 1898, Charles Branson set a 14"x10"x8" Basalt Rock 9" in the ground, and raised a mound of stones. No trees near

In 1961, Mervin Whitmore in Tillamook County Surveyors Re-Witness card #696, found a man-made rock mound on a steep west slope. Also found the marked stone with a visible "\$16", 50 feet down the slope on a bench. He reset the stone in the rock mound and marked: A 28" Fir, N 26 1/2° E, 37 ft. A 18" Fir, S 6 1/2° W, 18.5 ft.



Description of Corner Evidence found:

August 6, 1996, found the original stone marked "S16" in a mound of stone on a steep west slope, from which: A 38" Fir, N 26 $1/2^{\circ}$ E, 37.0 ft., healed blaze A 25" Fir, S 6 $1/2^{\circ}$ W, 18.5 ft., healed blaze (trees have BT and Attention signs)

Description of monument and accessories I established to perpetuate the original location of this corner:

I set a 5/8"x30" iron rod with a 3 1/4" Aluminum tablet in place of the original stone. (set stone alongside the new monument)


Set an orange fiberglass post with a "Land Survey Marker" decal next to the monument.

Painted Red Bands around the BT's.

Witness: Randy Zanon Equipment: Hand Compass Loggers Tape

Mag. Decl.: 19° East





REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JALY 18. 1980
MICHAEL J. SCHWARTZ
1922

EXPIRATION DATE: JUNE 30, 1998 MICHAEL J. SCHWARTZ 4077 SW RESEARCH WAY CORVALLIS, OR 97339

Office of SURVEYOR	County ofTILLAMOOH
	I hereby certify that the within instrument was
	575 day of SEPTEMBER, 1996
allan E. Vuncas, C.S.	by
(COUNTY OFFICIAL)	(DEPUTY)

FORM R6-7100-57 (9/71)