TILLAMOOK COUNTY SURVEYORS OFFICE 201 LAUREL AVENUE TILLAMOOK, OREGON 97141

SECTION CORNER COMMON TO SECTIONS 3, 4, 9, AND 10, T.2N.,R.7W.,W.M.

T2NR7W S4 | S3 S9 | S1 0 1952 PE | 2311

I FOUND A 1 1/2" IRON PIPE WITH 3" O.S.B.F. BRONZE CAP 15" HIGH, IN A MOUND OF STONE. FOUND ORIGINAL STONE, WITH NOTCHES LAYING DOWNHILL. I ENCASED THE FOUND IRON PIPE AND BRASS CAP IN AN IRREGULAR MASS OF CONCRETE AND STONES. I PLACED THE ORIGINAL STONE ON THE SW SIDE OF THE MONUMENT.

ACCESSORY EVIDENCE

I FOUND THIS CORNER TO BE AS DESCRIBED IN TILLAMOOK COUNTY SURVEYORS REWITNESS BOOK 5 AT PAGE 330 AND THE ACCESSORY EVIDENCE FOUND OR SET AT THAT TIME TO NOW BE AS FOLLOWS:

(ORIGINAL G.L.O.) 40" FIR S.69°E. 14 LINKS, REPORTED IN REWITNESS BOOK 2 AT PAGE 182 AS A 51" STUMP, FACE UNEXPOSED; AND REPORTED IN REWITNESS BOOK 5 AT PAGE 330 AS A 54" STUMP, FACE UNEXPOSED; (FOUND, NOW A 54" FIR STUMP, AT POSITION, FACE UNEXPOSED).

(REWITNESS BOOK 2 AT PAGE 182) 52' FIR STUB N.87°E. 78.4', REPORTED IN REWITNESS BOOK 5 AT PAGE 330 AS A 52' STUMP, FACE BURNT DUT, (FOUND, NOW A 52' FIR STUMP, 8' TALL, AT POSITION, FACE BURNT DUT, IN DLD LOGGING CAMP DUMP SITE).

(REWITNESS BOOK 2 AT PAGE 182) 50° FIR STUMP \$.63°W. 31.5^\prime) REPORTED IN REWITNESS BOOK 5 AT PAGE 330 AS A 50° STUMP, WITH SCRIBES VISIBLE) (FOUND, NOW A 50° FIR STUMP, 6^\prime TALL, AT POSITION, AXE MARKS VISIBLE).

(REWITNESS BOOK 2 AT PAGE 182) 48" FIR STUMP N.62°E, 24.0", REPORTED IN REWITNESS BOOK 5 AT PAGE 330 AS A 48" STUMP, WITH SCRIBES VISIBLE, (FOUND, NOW A 48" FIR STUMP, 4" TALL, AT POSITION, NO MARKS).

(REWITNESS BOOK 5 AT PAGE 330) 6" FIR N.23 3/4°W. 16.4" TO FACE; (FOUND, NOW A 20" FIR FACE HEALED OVER, AT POSITION, WITH D.S.B.F. YELLOW METAL LOCATION POSTER ATTACHED).

(REWITNESS BOOK 5 AT PAGE 330) 7" HEMLOCK N.89 3/4°E. 5.4' TO FACE, (FOUND, NOW A 14" HEMLOCK, SCRIBING VISIBLE ON PARTIALLY HEALED FACE, AT POSITION).*

(REWITNESS BOOK 5 AT PAGE 330) 10" HEMLOCK S.51 1/2"W. 29.2" TO FACE; (FOUND, NOW A 19" DOUBLE HEMLOCK, FACE HEALED OVER, AT POSITION).*

(REWITNESS BOOK 5 AT PAGE 330) 8" HEMLOCK S.11°E, 22.3" TO FACE; (FOUND, NOW AN 18" HEMLOCK, FACE HEALED OVER, AT POSITION).*

New Accessory

72" LIGHT HAT SECTION POST S.32°E, 1.73'.*

*INDICATES TILLAMOOK COUNTY SURVEYORS YELLOW METAL LOCATION POSTER ATTACHED.

LOCATION OF MONUMENT

THIS CORNER IS LOCATED APPROXIMATELY 100' WESTERLY OF STANDARD GRADE LOGGING ROAD, AN OLD RAILROAD LOGGING GRADE, WESTERLY OF AN OLD LOGGING CAMP DUMP SITE.

IN THE PRESENCE OF AL DVORAK AND DAN MCNUTT

DECEMBER 10, 1997

DEC 23 1997

OFFICE OFFICE

TITLE

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON JULY 14, 1967 ALLAN E. DUNCAN

793EXPIRES 12-31-97

BOOK 7 266