
# TILLAMOOK COUNTY SURVEYORS OFFICE COURT HOUSE, TILLAMOOK OREGON 97141

SECTION CORNER COMMON SECTIONS 2, 3, 10, and 11 T.IN., R.10V., V.M.



I FOUND A 1 1/2' IRON PIPE WITH A 3' D.S.B.F. BRASS CAP FLUSH WITH THE GROUND, (TILLAMOOK COUNTY SURVEYORS REWITNESS BOOK 1 AT PAGE 397). I SET A 10' CONCRETE CYLINDER AROUND THE MONUMENT.

## HISTORY OF FOUND MONUMENT

I FOUND THIS MONUMENT TO BE AS DESCRIBED IN TILLAMOOK COUNTY SURVEYORS REWITNESS CARD #16 AND THE REFERENCES FOUND OR SET AT THAT TIME TO NOW BE AS FOLLOWS:

(ORIGINAL G.L.O.) 12" HEMLOCK S.72°E. 38 LINKS, REPORTED IN REWITNESS BOOK 1 AT PAGE 397 AS NOW 20", SCRIBES "11 BT" VISIBLE, AND REPORTED IN REWITNESS BOOK 6 AT PAGE 272 AS 20" STUMP SCRIBES "11" VISIBLE ON TAP ROOT; (NOW, SAME AS REPORTED IN BOOK 6 AT PAGE 272).

(BDDK 1 AT PAGE 397) 23' HEMLDCK N.57 1/2'W. 42.4' REPORTED IN REWITNESS BOOK 6 AT PAGE 272 AS A 23' STUMP, 4' HIGH, SCRIBES "T1NR10WS3BT" VISIBLE; (NDW, 23' STUMP, 4' HIGH, NO SCRIBING VISIBLE).

(BOOK 1 AT PAGE 397) 20° DOUBLE HEMLOCK N.29°E. 10.8°, REPORTED IN REWITNESS BOOK 6 AT PAGE 272 AS 20° STUMP, 3' HIGH, PORTIONS OF SCRIBES VISIBLE; (NOW, 20° STUMP, VERY ROTTEN, NO MARKS).

(BDDK 1 AT PAGE 397) 46" HEMLDCK S.56 1/2°E, 32.8", REPORTED IN REWITNESS BDDK 6 AT PAGE 272 AS A 46" STUMP, 7" HIGH, SCRIBES "TINR10WS11BT" VISIBLE, (NDW, SAME AS REPORTED IN BDDK 6 AT PAGE 272).

(BDDK 1 AT PAGE 397) 24" HEMLDCK S.70 1/2°W. 2.0', REPORTED IN REWITNESS BDDK 6 AT PAGE 272 AS A 24" STUMP, 5' HIGH, SCRIBES "T1N" VISIBLE; (NDW, 24" VERY ROTTEN STUMP, 5' HIGH, WITH AXE MARKS).

(BOOK 6 AT PAGE 272) 10° FIR N.41°E. 13.7', (FOUND, NOW 12° FIR, FACE HEALED, AT POSITION, O.D.F. YELLOW METAL LOCATION POSTER ATTACHED).

(BOOK 6 AT PAGE 272) 11' FIR S.74 1/2'E. 7.5', (FOUND, NOW 14' FIR, FACE HEALED, AT POSITION, O.D.F. YELLOW METAL LOCATION POSTER ATTACHED).

(BOOK 6 AT PAGE 272) 13" FIR \$.34 1/2"W. 17.2") (FOUND, NOW 14" FIR, FACE HEALED, AT POSITION, D.D.F. YELLOW METAL LOCATION POSTER ATTACHED).

(BOOK 6 AT PAGE 272) 10° FIR N.69 1/2°W. 20.8°, (FOUND, NDW 12° FIR, FACE HEALED, AT POSITION, D.D.F. YELLOW METAL LOCATION POSTER ATTACHED).

THE 2 B.T.S, IN FIELD BK. "AMA 14" AT PG. 58 WERE SEARCHED FOR; (NOT FOUND). (BOOK 1 PAGE 397) 4"X 4"X 56" WHITE CEDAR POST 1.0" NE; (FOUND, NOW ROTTEN, LAYED ALONGSIDE NEW MONUMENT).

# NEW ACCESSORY

\*72' LIGHT HAT SECTION POST SOUTH 1.1', T.C.S. YELLOW METAL LOCATION TAG ATTACHED.

#### SURVEYS AND REWITNESSES OF RECORD

FIELD BOOK "AMA 14" PG. 58 B-419 B-437 REWITNESS BK 6 PG 272	07-30-1897 DECEMBER 1959 04-23-59 02-26-85	A. M. AUSTIN R. A. MORRIS R. A. MORRIS A. J. KLOSTERMAN	CS RS 401 RS 401 RS 1998
REWITNESS BK 1 PG 397	08-04-59	R. A. MORRIS	RS 401

### MONUMENT LOCATION

THIS MONUMENT IS LOCATED APPROXIMATELY 100' WEST OF A CREEK BOTTOM ON THE EASTERLY SLOPE OF A RIDGE, IN A STAND OF YOUNG HEMLOCK AND FIR.

IN THE PRESENCE OF DAN MCNUTT AND AL DVORAK

APRIL 15 1998

APR 29 1998

CLIVETORS OFFICE

Title

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
JULY 14, 1967
ALLAN E. DUNCAN
793

EXPIRES 12-31-99

7 272