

C 1/4 CORNER SECTION 26, T.3S.,R.9W.,W.M.

T3SR9W C1/4 . S26 LS 793 1998

I FOUND A 1 1/4" X 27" IRON PIPE WITH A WOOD PLUG AND NAIL 1" BELOW THE SURFACE. I SET A 1 1/2" IRON PIPE WITH A 3" TILLAMOOK COUNTY SURVEYORS BRASS CAP IN AN IRREGULAR MASS OF CONCRETE AND STONES, AT THE SAME POSITION AS THE FOUND 1 1/4" IRON PIPE.

HISTORY OF FOUND MONUMENT

THERE IS NO RECORD OF THE ORIGIN OF THE FOUND 1 1/4" IRON PIPE, HOWEVER, IT HAS BEEN USED FOR MANY YEARS TO POSITION TRACTS OF LAND IN THE AREA. EVIDENCE SEARCHED FOR OR FOUND IN THE VICINITY IS AS FOLLOWS:

(BOOK 1 PAGE 53) FIR POST FOR CORNER; (NOW GONE).

(BOOK 1 PAGE 53) 8" ALDER N.77"E. 1.06 CHAINS, REPORTED ON MAP F-40-138 AS A 30" ALDER N.77"E. 1.06 CHAINS; (NOW GONE).

(BOOK 1 PAGE 53) 6" FIR S.9"W. 0.71 CHAINS, REPORTED ON MAP F-40-138 AS A 24" FIR S.9"W. 71 LINKS; (NOW GONE).

(NO RECORD) FOUND HAT SECTION POST, 4' HIGH, NORTH 1.2' WITH YELLOW TILLAMOOK COUNTY SURVEYORS LOCATION POSTER ATTACHED, DATED 1968.

NEW ACCESSORIES

- *14" FIR S.73'52'E. 34.24' SCRIBED "BT" ON SMALL LOW FACE.
- *10" FIR S.12'43'W. 34.35' SCRIBED "BT" ON SMALL LOW FACE.
- *26" FIR N.20'48'W. 50.63' SCRIBED "BT" ON SMALL LOW FACE.
- * 4" HEMLOCK S.4679'W. 8.51' SCRIBED "BT" ON SMALL LOW FACE.

DISTANCES WERE MEASURED TO A T.C.S. BRASS WASHER NAILED BETWEEN THE "B" & "T".

"*" INDICATES YELLOW METAL TILLAMOOK COUNTY LOCATION POSTER ATTACHED.

SURVEYS A	ND REWITNESSES	OF RECORD	_
A-2899	JANUARY 1976	F. GAYLORD	LS 929
AMA FIELD NOTEBOOK 5 PAGE 39	MAY 21, 1903	A.M. AUSTIN	
REWITNESS BOOK 1 PAGE 53	MAY 21, 1903	A.M. AUSTIN	
REWITNESS BOOK 4 PAGE 7	MAY 21, 1903	A.M. AUSTIN	
SURVEY BOOK S3 PAGE 434	MAY 21, 1903	A.M. AUSTIN	
P-453	JUNE 24 1998	R. J. OLSEN	LS 701
A-5354	APRIL 1986	C.W. COOK	LS 1098
FIELD NOTEBOOK 53 PAGE 71	FEB. 29, 1928	W.S. COATES	CS
F-17-1	FEB. 29, 1928	W.S. COATES	CS
F-40-138	JUNE 1953	W.W. HUDSON	PE 2747
F-40-140	JUNE 1953	W.W. HUDSON	PE 2747
A-6590	APR. 27. 1993	D. KELLOW	LS 2027
A-3645	DECEMBER 1978	F. GAYLORD	LS 929
A-5909	JAN. 05. 1990	D. KELLOW	LS 2027
A-2930	APRIL 1976	F. GAYLORD	LS 929
A-2614	MAY 1974	F. GAYLORD	LS 929
F-2-13	1962	W.E. ANDERSON	CS

COMMENTS

THIS CORNER IS LOCATED APPROXIMATELY 180' SOUTHERLY OF THE CENTERLINE OF BEAVER—BLAINE COUNTY ROAD AND APPROXIMATELY 70' WEST OF A CREEK, 3' WIDE, IN AN OLD FENCE CORNER. REMAINS OF OLD WOOD POST AND BARB WIRE FENCE EAST—WEST. BARB WIRE FENCE WITH STEEL FENCE POSTS RUNS SOUTH FROM THE CORNER. DUE TO THE HIGH VISIBILITY OF THE AREA THE NEW BEARING TREES WERE MARKED WITH SMALL BLAZES AND SCRIBED "BT" ONLY.

THIS REWITNESS WAS MADE TO VERSEYE THIS MONUMENT ONLY. NO

ATTEMPT WAS MADE TO VERIFY THE LOCATION OF THIS MONUMENT.

IN THE PRESENCE OF AL DVORAK AND DAN MCNUTT

DECEMBER 22, 1998

TITLE

REGISTERED **PROFESSIONAL** LAND SURVEYOR Allan E. Duncan, c.s.

THE AMOON COUNTY

JAN 21 1999

PETORS OFFICE

OREGON JULY 14, 1967 ALLAN E. DUNCAN 793

EXPIRES 12-31-99