TILLAMOOK COUNTY SURVEYORS OFFICE COURT HOUSE, TILLAMOOK OREGON 97141 SECTION CORNER COMMON TO SECTIONS 7, 8, 18, & 17, T.1S.,R.10W.,W.M.

TISR10W S 7 | S 8 S18 | S19 LS 287 1978

I FOUND A 2" IRON PIPE WITH A 3" TILLAMOOK COUNTY SURVEYORS BRASS CAP IN A 10" TILE FILLED WITH CONCRETE STAMPED AS SHOWN AT LEFT.

HISTORY OF FOUND MONUMENT

I FOUND THIS MONUMENT TO BE AS DESCRIBED ON TILLAMOOK COUNTY REWITNESS CARD #282. AND THE REFERENCES FOUND OR SET AT THAT TIME TO NOW BE AS FOLLOWS:

(G.L.O.) 24" HEMLOCK N.37"E. 50 LINKS, REPORTED IN REWITNESS #282 AS "FOUND, 36" SNAG, 15' HIGH, SCRIBING VISIBLE"; (FOUND, NOW 3' HIGH, 36" DIAMETER ROTTED SNAG).

(Bk. 4 Pg. 97) 20" HEMLOCK S.5"E. 116.6'; REPORTED IN REWITNESS #282 AS "FOUND, GOOD, NOW 24""; (NOW, GONE).

(Bk. 4 Pg. 97) 14" HEMLOCK N.26"W. 18.5'; REPORTED IN REWITNESS #282 AS "FOUND, GOOD, SCRIBING VISIBLE, NOW 20""; (FOUND, NOW 23", 8' HIGH STUMP, SCRIBING VISIBLE, AT POSITION).

(Bk. 3 Pg. 9) 24" HEMLOCK S.31'30'W. 105.7'; REPORTED IN REWITNESS #282 AS "FOUND, 30" UPROOT"; (FOUND, NOW AN UPROOT).

(Bk. 3 Pg. 9) 28" HEMLOCK N.19"E. 17.8'; REPORTED IN BOOK 4 AT PAGE 97 AS N.22"E. 16.4', AND REPORTED IN REWITNESS #282 AS "FOUND, 36" STUMP WITH FACE & SCRIBE MARKS"; (FOUND, NOW A ROTTED STUMP).

*(REWITNESS #282) 16" HEMLOCK N37"E. 39.25"; (FOUND, NOW A 14" SNAG 30' TALL, SCRIBING VISIBLE ON PARTIALLY HEALED FACE).

*(REWITNESS #282) 72" HAT SECTION POST WEST 1.5"; (FOUND, AT POSITION).

NEW ACCESSORIES

- *16" HEMLOCK N.18'55'W. 25.24', SCRIBED "T1SR10WS7BTCS"
- *10" HEMLOCK N.56"11'E. 30.51', SCRIBED "T1SR10WS8BTCS"
- *15" ALDER S.60"16'E. 9.37', SCRIBED "T1SR10WS17BTCS"
- *6" HEMLOCK S.64"34"W. 10.75", SCRIBED "T1SR10WS18BTCS"
- *INDICATES TILLAMOOK COUNTY SURVEYORS YELLOW METAL LOCATION POSTER ATTACHED.

BASIS OF BEARINGS IS N.2°46'31"E. BETWEEN THIS SECTION CORNER AND THE MEANDER CORNER BETWEEN SECTIONS 7 & 8 T.1S.,R.10W.,W.M., AS COMPUTED FROM FROM MAP F-13-28.

SURVEYS AND REWITNESSES OF RECORD

SEE REWITNESS BIN CARD #282 MARCH 1978 JOHN L CARLICH C.S. FOR DETAILED REPORT OF PRIVIOUS REFERENCE SURVEYS AND RESTORATIONS.

MONUMENT LOCATION

THIS MONUMENT IS LOCATED 25' NORTH OF CAPE MEARES COUNTY ROAD IN AN AREA THAT HAS BECOME VERY PRONE TO SLIDES. A TIE TO THE 1/4 CORNER AND THE MEANDER CORNER NORTH INDICATES THAT THE CORNER ITSELF IS STILL IN ITS' ORIGINAL LOCATION.

IN THE PRESENCE OF DAN MCNUTT AND AL DVORAK

TITLE:

PROFESSIONAL LAND SURVEYOR

OREGON JULY 14, 1967 ALLAN E. DUNCAN 793

EXPIRES 12-31-99

MAR 24 1999

THEFORS OFFICE

TILLAMOON COL

MARCH 17.

291