## RESTORED CORNER FOR OREGON DEPARTMENT OF FORESTRY 4907 Third St., Tillamook, Oregon 97141

Section corner common to Sections 25, 26, 35 and 36, T2N, R8W, W.M.; Tillamook County, Oregon.

ORIGINAL by Henry Meldrum, August 20, 1891.

16"x9"x7" Basalt stone with 1 notch on South and East edges; found a 12"x9"x4" broken Basalt stone with 1 notch, disturbed but at corner point.

60" Fir bears N50½°E 18 lks.; now 60"x5 ft. high rotted stump with scribes T2N R7W S25 visible.

50" Fir bears S66°E 58 lks.; missing.

18" Hemlock bears S47°W 51 lks.; missing. 9" Hemlock bears N75°W 26 lks.; missing.

NOTE: Other 1891 corners for this township are known to be set from the BT face.

ERRONEOUS RESTORATION by Louis W. Amort RE2311 December 11, 1952 (Book 2, page 248, Tillamook County Records).

NOTE: Meldrum's 60" Fir (NE BT) mistaken for his 50" Fir (SE BT).

 $1\frac{1}{2}$ "x36" Galvanized iron pipe with 3" bronze cap, 30" in ground, in raised mound of stone; now 40" in ground, in place.

66" Fir stub 8 feet high bears N48°E 11.4 ft.; now a 4 ft. high badly rotted stump with scribes R8W S25 BT RE2311 visible.

54" Fir stump bears S34½°W 72.6 ft.; now 7 ft. high and rotted with

scribes T2N R8W S35 BT visible.

48" Fir snag bears N66°W 63.4 ft.; now a 7 ft. high rotted stump with scribes T2N R8W S26 BT visible.

RESTORED August 23, 2000

Var. 18½°E

Set 1½"x40" Galvanized iron pipe with 3 3/4" bronze cap marked "STATE OF OREGON DEPARTMENT OF FORESTRY T2N R8W S26 S25 S35 S36 2000 LS1998", 36" in Ground, placed original stone on North edge and from which a:

15" Fir bears N342°E 31.4 ft. to face; scribed T2NR8WS25BT.

13" Fir bears S78½°E 13.4 ft. to face; scribed T2NR8WS36BT.

14" Fir bears S36½°W 39.6 ft. to face; scribed T2NR8WS35BT.

20" Fir bears N76½°W 11.3 ft. to face; scribed T2NR8WS26BT.

SHEET 1 of 2

ANLLA OOK OCT 12 2000 Terors of

SURVEYED BY:

REGISTERED **PROFESSIONAL** LAND SURVEYOR

g. Klasterman anthony OREGON

July 21, 1982 Anthony J. Klosterman 1998

4907 THIRD STREET TILLAMOOK, OR 97141 EXPIRES JUNE 30, 2001 Amort's pipe bears N46½°W 36.8 ft. with marks "RM LS1998-2000 36.8 ft." added and driven 42" in ground.

Metal location poster on new Bts.

3/4" brass washer marked "LS1998" nailed to face of new Bts. 6 foot Orange carsonite post bears S76°W 1.1 ft. Destroyed scribe marks on Amort's Bts. Present and witnessed by Clifford R. Foster, Chris R. Woodward and J. Clint Smith.

Restored by  $\frac{\mathcal{D}_{aved} \ \mathcal{B}. \ \mathcal{B}_{uchhof}}{\text{David B. Buchholz, LS2272}}$  under my direction.

SHEET 2 of 2

(\*\*\*00x co) 000 21 130 Erons of

SURVEYED BY:

REGISTERED **PROFESSIONAL** LAND SURVEYOR

OREGON
July 21, 1982
Anthony J. Klosterman
1998

4907 THIRD STREET TILLAMOOK, OR 97141 EXPIRES JUNE 30, 2001