REWITNESSED CORNER FOR OREGON DEPARTMENT OF FORESTRY 4907 Third St., Tillamook, Oregon 97141

One quarter corner common to Sections 26 and 27, T3N, R8W, W.M., Tillamook County, Oregon.

ORIGINAL by Henry Meldrum, October 14, 1891.

20"x10"x5"Basalt stone 15" in ground with ¼ on west face; found 12"x6"x4" Basalt stone scribed ¼, on North edge of pipe.

- 16" Hemlock bears N50°E 16 lks.; now a 16" x 9 ft. uproot, no scribes visible.
- 10" Hemlock bears S30°W 13 lks.; now missing.

RESTORATION by Louis W. Amort RE2311, April 7, 1952 (Book 2, page 143, Tillamook County Records).

1 1/2"x36" galvanized iron pipe with 3" bronze cap, 30" in ground, in mound of stone; in place.

- 42" Fir stump bears S54%°E 4.9 ft.; now a 42" x 3 ft. high and badly rotted with no scribes visible.
- 42" Fir snag bears N48½°W 21.1 ft.; now a 42" x 3½ ft. high rotted stump with scribes ½ S27 BT 2311 visible.

NOTE: Amort called a bearing of N50°W to the original 16" Hemlock with scribing found. The corner appears to have been set properly with a recording error in the bearing, based on evidence found. The original stone was found out of place in 1952.

RESTORED April 11, 2001

Var. 18½°E

From above pipe with marks "LS1998-2001" added a:

- 14" Fir bears N12°E 21.95 ft. to face; scribed 1/4S26BT.
- 11" Fir bears S75°E 19.1 ft. to face; scribed 1/4S26BT.
- 11" Fir bears S40½°W 17.0 ft. to face; scribed 1/4S27BT.
- 21" Fir bears N81%°W 9.9 ft. to face; scribed 1/4S27BT.

Metal location poster on new BTs. Also on Amort's BTs. 3/4" brass washer marked "LS1998" nailed to face of new BTs. 6 ft. orange carsonite post bears NO7°W 2.95 ft. Present and witnessed by Clifford R. Foster.

Rewitnessed by <u>David B. Buchhol</u> under my direction.

David B. Buchholz, LS2272

SURVEYED BY:

REGISTERED PROFESSIONAL LAND SURVEYOR

anthony J. Klasterman

OREGON
July 21, 1982
Anthony J. Klosterman
1998

4907 THIRD STREET TILLAMOOK, OR 97141 EXPIRES JUNE 30, 2001

