TILLAMOOK COUNTY SURVEYORS OFFICE COURTHOUSE, TILLAMOOK, OREGON 97141

1/4 CORNER COMMON SECTIONS 4 & 5 T.2S.; R.10W.; W.M.

LS 849 1/4 | | S5 + S4 | CZ 1974

I FOUND A 2" IRON PIPE WITH A 3" CROWN ZELLERBACH BRASS CAP FLUSH IN 10" TILE FILLED WITH CONCRETE, SEE TILLAMOOK COUNTY SURVEYORS REWITNESS CARD #443.

HISTORY OF FOUND MONUMENT

I FOUND THIS MONUMENT TO BE AS DESCRIBED ON TILLAMOOK COUNTY SURVEYORS REWITNESS CARD #443 AND THE REFERENCES FOUND AND/OR SET AT THAT TIME TO NOW BE AS FOLLOWS:

(MAP B-659) 18" SPRUCE N.44 1/2° W. 43.54'; REPORTED ON REWITNESS #443 AS 24" SPRUCE; FOUND, NOW A 24" STUMP, 5.5' TALL, FACE HEALED, TAGS STILL ATTACHED, AT POSITION.

(MAP B-659) 36" SPRUCE S.47° W. 43.44'; REPORTED ON REWITNESS #443 AS A 40" SPRUCE; FOUND, NOW A 40" STUMP 6.5' TALL, FACE ROTTED, TAGS STILL ATTACHED, AT POSITION.

4" X 4" X 48" POST, FOUND ROTTED OFF AND LAYING BESIDE CORNER MONUMENT.

	SURVEYS AND REWITNESSES OF	RECORD	
B-659	APRIL 8, 1974	CARL FOESTE LS 849	9
B-658	APRIL 15, 1974	CARL FOESTE LS 849	9
F-20-20	JUNE 1990	ALLAN E. DUNCAN LS 793	3

NEW ACCESSORIES

*10" SPRUCE N. 2° W. 4.15' 1/4S5BTCS MEASUREMENTS WERE TAKEN TO A BRASS WASHER AND NAIL BETWEEN THE "B" & "T" IN THE FACE OR THE TREE.

*7" SPRUCE S. 54° E. 11.29' 1/4S4BTCS MEASUREMENTS WERE TAKEN TO A BRASS WASHER AND NAIL BETWEEN THE "B" & "T" IN THE FACE OR THE TREE.

*LIGHT HAT SECTION POST SOUTH 1.35'.

"*" INDICATES YELLOW METAL TILLAMOOK COUNTY LOCATION POSTER ATTACHED.

LOCATION OF MONUMENT

THIS CORNER IS LOCATED ON THE EAST SIDE OF THE TOP OF A SPUR RIDGE APPROXIMATELY 150' SOUTH OF STATE HIGHWAY 131 (NETARTS HIGHWAY).

IN THE PRESENCE OF AL DVORAK AND DAN MCNUTT

SEPTEMBER 11, 2001



REGISTERED
PROFESSIONAL
LAND SURVEYOR

Allan & Duncan, C. S.

OREGON
JULY 14, 1967
ALLAN E. DUNCAN
7 9 3

BOOK 7 346