BAYSIDE SURVEYING

11765 HWY 101 South Tillamook, Oregon 97141

Terry L. Jones 503-842-5551 Fax 503-842-5552

April 2002 REWITNESS

SECTION CORNER COMMON TO SECTIONS 28, 27, 33 & 34 TOWNSHIP 2 SOUTH, RANGE 8 WEST

I found:

HELD, BLM brass cap on $1\frac{1}{2}$ iron post stamped "T2S R8W S28 S27 S33 S34 1956" in stone mound. (See BLM field notes.)

OSBF brass cap on $1\frac{1}{2}$ " iron pipe stamped "T2S R8W S28 S27 S33 S34 1953 2311", South 0.09' and West 0.15' of BLM BC, Rewitness Book 2 Page 302, NOT HELD. (See BLM field notes.)

From which: GLO BT:

34" rotten stump bears S62°W 16 lks. (34" burned snag bears S62°W 16 lks. See BLM field notes.) Note: SE & NW BT's are now gone

BLM BTs:

33" burnt stump with some scribing bears N52°E 35 lks. (33" burnt stump bears N52°E 35 lks. See BLM field notes.)

rotten stub, no scribing, bears S23.5°E 89 lks. (20" burned stub bears S22.5°E 89 lks. See BLM field notes.)

rotten stub, no scribing, bears $S84^{\circ}W$ 39 lks. (18" burned snag bears $S84^{\circ}W$ 39 lks. See BLM field notes.)

50" burnt snag no scribing bears N50% W 87 lks. (50" burned snag bears N50% W 87 lks. See BLM field notes.)

I set:

Carsonite post 4' North, and 4 New BTs as follows:

12" Hemlock scribed "T2S R8W S34 BT" bears S65°E 25.9' to brass nail & washer stamped "LS 2507" between the B & T;

9" Hemlock scribed "T2S R8W S27 BT" bears N41°E 15.9' to brass nail & washer stamped "LS 2507" between the B & T;

15" Douglas Fir scribed "T2S R8W S28 BT" bears N28°W 13.3' to brass nail & washer stamped "LS 2507" between the B & T;

14" Douglas Fir scribed "T2S R8W S33 BT" bears S45°W 15.3' to brass pair & washer stamped "LS 2507" between the B & T:

STAC

Inputhe presence of Terry Jones, Dallas Esplin

OMEGON
JULY 25, 1991
TERRY L. JONES

REGISTERED

PROFESSIONAL LAND SURVEYOR

BOOK 7 362