TILLAMOOK COUNTY SURVEYORS OFFICE COURTHOUSE, TILLAMOOK, OREGON 97141

1/4 CORNER COMMON TO SECTION 36, T.2 N., R.10 W. M., AND SECTION 31, T.2 N., R.9 W., W. M.

I FOUND AN OREGON STATE BOARD OF FORESTRY IRON PIPE AND BRASS CAP, STAMPED AS SHOWN HEREON. I ENCASED THE FOUND MONUMENT IN A 10" DIAMETER CONCRETE CYLINDER AND A MOUND OF STONES.

1/4 S36 | S31 1968 RS707

HISTORY OF FOUND MONUMENT

THE MONUMENT WAS FOUND AS DESCRIBED IN REWITNESS BOOK 3, PAGE 263, AND THE ACCESSORIES FOUND AND/OR SET AT THAT TIME TO NOW BE AS FOLLOWS:

BOOK 2, PAGE 189, SCRIBED A 50" HEMLOCK TREE BEARING NORTH 52° EAST 10.8'; BOOK 3, PAGE 263 FOUND A 60" STUMP; 08-02-05 FOUND ROOT CROWN AT RECORD POSITION, BUT STUMP IS GONE.

BOOK 2, PAGE 189, SCRIBED A 24" HEMLOCK TREE BEARING SOUTH 84° WEST 21.5"; BOOK 3, PAGE 263 FOUND A 30" SNAG; 08-02-05 FOUND 30" DIAMETER ROTTEN STUMP AT RECORD POSITION, 2.0" HIGH, NO MARKS VISIBLE.

BOOK 3, PAGE 263, SCRIBED A 27" HEMLOCK TREE BEARING SOUTH 80° EAST 39.6'; 08-02-05 FOUND 27" DIAMETER ROTTEN STUMP AT RECORD POSITION, 2.0' HIGH, NO MARKS VISIBLE.

BOOK 3, PAGE 263, SCRIBED A 48" HEMLOCK TREE BEARING SOUTH 29° WEST 31.9'; 08-02-05 FOUND 48" DIAMETER ROTTEN STUMP AT RECORD POSITION, 6.0' HIGH, NO MARKS VISIBLE.

BOOK 3, PAGE 263, SET A 4" X 4" X 60" WHITE CEDAR POST 1.0' NW OF CORNER PIPE. 08-02-05 FOUND WHITE CEDAR POST AS DESCRIBED IN BOOK 3, PAGE 263.

SURVEYS AND REWITNESSES OF RECORD

B-389 1958 JOHN L. CARLICH LS 287 B-565 JULY 1968 HAROLD J. RUSSEL LS707 BOOK 2, PAGE 189, 1951 W.A. MARKHAM RE 1842 BOOK 3, PAGE 263, JULY 1968 HAROLD J. RUSSEL LS707

NEW ACCESSORIES

*21" DIAMETER HEMLOCK BEARING NORTH 88° WEST 20.67' SCRIBED "T2NR9WS31BTCS". DISTANCE WAS MEASURED TO A BRASS WASHER STAMPED "T.C. SURV" NAILED TO THE FACE BETWEEN THE SCRIBED 'B' & 'T'.

*21" DIAMETER HEMLOCK BEARING NORTH 71° WEST 8.12' SCRIBED "T2NR10WS36BTCS". DISTANCE WAS MEASURED TO A BRASS WASHER STAMPED "T.C. SURV" NAILED TO THE FACE BETWEEN THE SCRIBED 'B' & 'T'.

Page 1 of 2

- *20" DIAMETER HEMLOCK BEARING SOUTH 24° WEST 41.16' SCRIBED "T2NR10WS36BTCS". DISTANCE WAS MEASURED TO A BRASS WASHER STAMPED "T.C. SURV" NAILED TO THE FACE BETWEEN THE SCRIBED 'B' & 'T'.
- *SET ORANGE CARSONITE POST NORTH 2.00 FEET.
- * INDICATES TILLAMOOK COUNTY YELLOW METAL LOCATION POSTER ATTACHED

LOCATION OF MONUMENT

THIS ONE-QUARTER CORNER IS LOCATED APPROXIMATELY 10' SOUTH OF THE TOP OF A CUT BANK OF A NEWLY CONSTRUCTED LOGGING ROAD.

IN THE PRESENCE OF, AND REWITNESSED BY DANNY R. MCNUTT, TILLAMOOK COUNTY SURVEYOR AND JOE JENSEN, SURVEY SUPERVISOR.

AUGUST 02, 2005

TITLE:

REGISTERED
PROFESSIONAL
LAND SURVEYOR

my R me nutt

OREGON JULY 11, 2000 DANNY R. MCNUTT 49230

RENEWAL12-31-06

