## OREGON PUBLIC LAND CORNER REPORT / RESTORATION REPORT Tillamook County Surveyor's Office


SECTION: 5, 6, 7 and 8	TOWNSHIP 1 North	RANG	NGE 10 West	
COUNTY: Tillamook				DATE: 08-06-15
CORNER DESIGNATION:	The Section Corner common to	5, 6, 7 and 8,	1000	(Please check one)
Township 1 North, Range 10 west, W.M.			×	Condition Report Only
				Restoration
				Rewitness
				Unrecorded
				Reset
			×	Referenced Out
Previous Rewitnesses, Res 7989; Tillamook County Surv		Rewitness Car	A SECTION AND ADDRESS.	S; Rewitness Book 7, Page 227; Map A-
Found Monument(s) and A diameter cast iron monumen hereon. Found a 72" light hat section	t case in concrete. The monume	ce): Found 3" ent is in good o	diam condi	eter Tillamook County Brass Cap in an 8" tion. The monument is stamped as shown
Monument Set (Procedures and Description): Not Applicable. The purpose of this corner report is to set two reference monuments to the corner and obtain GPS coordinates on both new accessories. A conventional field tie was made from the two newly set reference monuments to the section corner. This coordinate value was then averaged with the existing GPS location of the corner. The datum for the horizontal grid coordinates is NAD '83-'91 State Plane Coordinates, Oregon North Zone, U.S. Foot.			Sketch of Found Monument:	
Coordinate location for the Section Corner: N=721894.284; E=7320031.469; Latitude = 45°35'42.50933" N, Longitude = 123°56'49.00191" W				S6 S5 S7 S8 LS 793 1996
Convergence = -2°26'40.525 Grid Scale Factor = 0.999922				
of U.S. Highway 101. Coordii 45°35'41.61396" N, Longitud Set a 5/8" x 30" rebar with a	nate location for this Reference I le = 123°56'50.03780" W. red plastic cap stamped "TILLAN reference Monument: N=721900	Monument: No	=7218 RVE	LLAMOOK CO SURVEY" on the West side 806.824; E=7319954.013; Latitude =  Y" on the East side of U.S. Highway 101. 801; Latitude = 45°35'42.57968" N,
New Bearing Trees: No new	bearing trees were set.			
the centerline of U.S. Highwa concrete box culvert for the c	s corner is located approximately by 101 and approximately 40' No outlet of Spring Lake and approxi Port of Tillamook Bay Railroad.	rth of a		
Firm / Agency Address: TILLAMOON 1510 Th	COUNTY SURVEYOR'S OFFI nird Street, Suite C ok, Oregon 97141	CE		SURVEYOR'S SEAL  REGISTERED

G:\completed restorations\T1NR10WS5,6,7,8.doc

Party Chief: Joe Jensen, PLS 60067, Survey Supervisor

Notes: Digital photos have been taken of the monument.

Witness: Danny R. McNutt, PLS 49230, Tillamook County Surveyor Michael R. Rice, PLS 86926, Survey Technician



JOSEPH V. JENSEN

PREMIUM DATE: 08-30-17