NER INVESTIGATION A

FS INDEX ID: R-6

WEST 1/16 CORNER:

GCDB ID: 220300

DATE: 3/3/2017

TOWNSHIP: 3S 8W RANGE: 20 & 29 SECTION:

MERIDIAN: WILLAMETTE

STATE: OREGON COUNTY: TILLAMOOK FOREST: SIUSLAW DISTRICT: HEBO

NFSL PROPERTY BOUNDARY CORNER?: YES NO

SOUTH - 1978 WEST - 1978 LINE(S) POSTED: SOUTH - 2017 WEST - 2017 MAINTAINED: SOUTH - 2.6 FT WEST - 2.3 FT GUARD POST(S):

CORNER HISTORY: (1978) - ESTABLISHED CORNER BY PROPORTION BY SURVEY, SETS GALVANIZED IRON PIPE WITH A BRASS CAP & 2 BT'S.

(1979) - FOUND MONUMENT & BT'S PER CSF# B-802

(1982) - FOUND BRASS CAP

(1996, 1998, 2003, 2004 & 2008) - FOUND A 2.5" BC ON 2" GIP WITH BT'S PER B-802.

(2005) - FOUND BRASS CAP

MONUMENT FOUND/SET: FOUND A 1-1/4" GALVANIZED IRON PIPE WITH A 2-1/2" BRASS CAP, DOWN 1" BELOW GROUND.

RECORD CORNER ACCESSORIES:
A 29" FIR BEARS, S2°08'E - 37.4 FT, WITH A HEALED SINGLE BLAZE.
A 27" FIR BEARS, N74°58'E - 29.2 FT, WITH A HEALED SINGLE BLAZE.
A 1" GALVANIZED IRON PIPE BEARS, N25°11'W - 5.7 FT, PROJECTING 3 INCHES

ABOVE THE GROUND. NO RECORD OF SOURCE LOCATED.

A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP BEARS, S00°36'22"W - 1050.01 FT, FOR WITNESS CORNER, NW 1/16. FLUSH WITH GROUND.

HISTORY OF VISITATIONS: 1978 - K.F. FOESTE, CSF# B-802 1979 - H.L. RICKS, CSF# B-826 1982 - F.M. GAYLORD, CSF# B-1076

1996 - T.L. JONES, CSF# B-2020 1998 - T.L. JONES, CSF# B-2195 2003 - T.L. JONES, CSF# B-2695

2004 - T.R. JONES, CSF# A-7914 2005 - C.W. COOK, CSF# B-2938 2008 - T.L. JONES, CSF# B-3221

> REGISTERED PROFESSIONA LAND SURVEYOR

onthon B. Drawt OREGON JONATHAN B. DREW II 89395

EXPIRES: 12/31/2017 (S3°E - 36.65 FT TO FACE)1978 (N68°E - 28.9 FT TO FACE)1978 NO RECORD

(S00°36'22"W - 1050.00 FT)1979

NEW CORNER ACCESSORIES: NO NEW ACCESSORIES ADDED.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

DOCUMENTS ON FILE AT:

3106 PIERCE PARKWAY, STE D SPRINGFIELD OREGON, 97477

PHONE: (541)-225-6474

GEODETIC COORDINATES:

LATITUDE: N 45° 17' 13.104" LONGITUDE: W 123° 42' 05.520"

ELLIPSOID HEIGHT:

DATUM: WGS 84

SOURCE: POSITION ESTIMATED FROM GEOREFERENCED ORTHO PHOTO.

DATE OF INVESTIGATION: 3/1/2017

REPORT BY: JONATHAN B. DREW II, PLS# 89396, CFedS# 1664

ASSISTED BY: ANDREW HILLMAN, SURVEY TECH. JACOB HUNT, SURVEY TECH.

METHOD OF MEASUREMENT: TRIMBLE S7 TOTAL STATION

BEARING BASIS: CSF# B-826 HOLD RECORD BEARING OF S00°36'22"W TO WC NW 1/16 S29, TIED BY TRAVERSE.

BT BEARINGS TO CENTER DISTANCES TO AN ALUMINUM NAIL SET AT SIDE CENTER

CAP DIAGRAM:

18849 S20 16 S29 1978

THIS DOCUMENT FILED IN CS OFFICE: YES OTHER DOCUMENT FILED WITH CS: NONE

