## CORNER INVESTIGATION REPORT

FS INDEX ID: T-22

CENTER WEST 1/16 GCDB ID: 620240 CORNER:

DATE: 6/11/2018

HISTORY OF VISITATIONS:

(1)1985 - L. BISHOP, CSF# B-1196

OREGON TOWNSHIP: 3S STATE: COUNTY: TILLAMOOK 8W <u>RANGE:</u>

25 SECTION:

SIUSLAW FOREST:

MERIDIAN: WILLAMETTE

**DISTRICT:** HEBO

NFSL PROPERTY BOUNDARY CORNER?:

☑YES □NO

LINE(S) POSTED: NORTH - 1985

SOUTH - 1985

MAINTAINED:

NORTH - NONE

SOUTH - 2017

GUARD POST(S):

NONE

NONE

CORNER HISTORY:

(1) ESTABLISHED CORNER BY SURVEY, SET ALUMINUM PIPE/CAP FOR CORNER & RM, MARKED 1 BT.

REGISTERED **PROFESSIONAL** LAND SURVEYOR

reut OREGON JONATHAN B. DREW II

EXPIRES: 12/31/2019 RECORD MEASUREMENTS:

MONUMENT FOUND/SET:

FOUND A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP, DOWN 4" BELOW ROAD GRADE. CORNER LOCATED IN THE EASTERLY TRAVEL LANE OF A GRAVELED ROAD.

RECORD CORNER ACCESSORIES:

A 40" FIR STUMP BEARS, N60°45'W - 47.9 FT, WITH A HEALED DOUBLE BLAZE.

AN ALUMINUM PIPE/CAP RM BEARS, S17°57'W - 54.39 FT, DOWN 4 INCHES BELOW (1)S17°57'W - 54.3 FT GROUND LEVEL & MARKED AS DESCRIBED IN (1).

(1)N61°W - 48.2 FT

NEW CORNER ACCESSORIES:

A 9" FIR BEARS, N45°32'W - 32.4 FT, MARKED "CW1/16S25""BT" ON DOUBLE BLAZE.

NEW BT INCLUDES A 3/4" BRASS WASHER NAILED BETWEEN "B"&"T" SCRIBES.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NFSL LINES BEAR: (1)S0°54'03"E - 1281.59 FT & (1)N0°46'38"W - 1275.81 FT.

GEODETIC COORDINATES:

**DOCUMENTS ON FILE AT:** 

LATITUDE: N 45° 16' 50.933" LONGITUDE: W 123° 37' 18.211" WILLAMETTE NATIONAL FOREST 3106 PIERCE PARKWAY, STE D SPRINGFIELD, OREGON 97477

**ELLIPSOID HEIGHT:** 

DATUM: WGS 84

SOURCE: USGS QUAD MAP, FOR NAVIGATION TO CORNER.

DATE OF INVESTIGATION: 11/27/2017

REPORT BY: JONATHAN B. DREW II, PLS #89396, CFedS #1664

FIELD CREW: JACOB HUNT, USFS SURVEY TECH.

ANDREW HILLMAN, USFS SURVEY TECH.

METHOD OF MEASUREMENT:

HOLD RECORD BEARING OF (1)S17°57'W TO REFERENCE MONUMENT SET IN 1985. MEASURMENTS MADE WITH TRIMBLE S7 TOTAL STATION, DISTANCES TO AN ALUMINUM NAIL SET SIDE CENTER OF BT'S AND TO CENTER OF RM, BEARINGS TO CENTER.

CAP DIAGRAM:



THIS DOCUMENT FILED IN CS OFFICE: YES

OTHER DOCUMENT FILED WITH CS: RECORD OF SURVEY FILED SEPARATELY