# CORNER INVESTIGATION REPORT

OREGON

## FS INDEX ID: V-23

CORNER: 1/4 TOWNSHIP: 3S

RANGE:

GCDB ID: 640200 STATE:

DATE: 6/11/2018

#### HISTORY OF VISITATIONS:

(1)1884 - H. MELDRUM, GLO SURVEY (2)1967 - B. UDELL, CSF# A-1405 & RW3/61

(3)1969 - H. RUSSELL, CSF# B-598 (4)1985 - L. BISHOP, CSF# B-1191

SECTION: 25 & 36 MERIDIAN: WILLAMETTE

8W

FOREST: SIUSLAW

COUNTY: TILLAMOOK

NFSL PROPERTY BOUNDARY CORNER?:

**DISTRICT:** HEBO

LINE(S) POSTED:

☑YES □NO WEST - 1985 SOUTH - 1985

**MAINTAINED:** 

SOUTH - 2017

WEST - NONE

**GUARD POST(S):** 

SOUTH - 4 FT WEST - 3.5 FT

#### **CORNER HISTORY:**

(1) ESTABLISHED CORNER, SET POST & 2 BT'S.

(2) FOUND OLD SQUARED POST & FS TAGS ON 2 LARGE ALDERS OF NO RECORD. RE-ESTABLISHED CORNER BY PROPORTION, SET PIPE/BRASS CAP & 2 BT'S.

(3) FOUND IRON PIPE/BRASS CAP.

(4) FOUND IRON PIPE/BRASS CAP & 2 BT'S, SET ALUMINUM PIPE/CAP RM.

## MONUMENT FOUND/SET:

FOUND A 2-1/2" GALVANIZED IRON PIPE WITH A 2-1/2" BRASS CAP, PROJECTING 12 INCHES ABOVE THE GROUND.

# RECORD CORNER ACCESSORIES:

NO TRACE FOUND OF A (1)4" MAPLE

NO TRACE FOUND OF A (1)3.5" BARBERRY.

A 43" ALDER WITH NO MARKS VISIBLE ON A PREVIOUSLY OPENED FACE.

A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP FOR REFERENCE MONUMENT, MARKED AS DESCRIBED IN (4). NOTE: MONUMENT LOCATED IN

REGISTERED PROFESSIONAL LAND SURVEYOR

outhern Bibeutt OREGON JONATHAN B. DREW II

89396

EXPIRES: 12/31/2019 RECORD MEASUREMENTS:

(1)S34°W - 10.56 FT

(1)N30°30'W - 9.9 FT

(2,4)N7°E - 9.2 FT

A 28" FIR STUMP WITH SCRIBE VISIBLE ON A PARTIALLY HEALED SINGLE BLAZE. (2)S42°W - 51.7 FT, (4)S40°W - 30.8 FT

(4)S7°37'E - 45.85 FT (S7°37'W PER CAP)

SW QUADRANT AS PER CAP MARKINGS NOT SE AS PER RECORD BEARING.

# **NEW CORNER ACCESSORIES:**

NO NEW ACCESSORIES ESTABLISHED.

## METHOD OF MEASUREMENT:

NO NEW MEASURMENTS TAKEN, FILED AS CONDITION REPORT.

# CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NFSL LINES BEAR: (4)S0°04'55"E - 2712.72 FT & (4)N88°23'55"W - 2548.45 FT

GEODETIC COORDINATES:

DOCUMENTS ON FILE AT:

LATITUDE: N 45° 16' 25.082" LONGITUDE: W 123° 37' 0.174" ELLIPSOID HEIGHT: ~1210 FT

WILLAMETTE NATIONAL FOREST 3106 PIERCE PARKWAY, STE D SPRINGFIELD, OREGON 97477

DATUM: WGS 84

SOURCE: CONSUMER GRADE GPS, FOR NAVIGATION TO CORNER

DATE OF INVESTIGATION: 11/28/2017

REPORT BY: JONATHAN B. DREW II, PLS #89396, CFedS #1664

FIELD CREW: JACOB HUNT, USFS SURVEY TECH. ANDREW HILLMAN, USFS SURVEY TECH.

THIS DOCUMENT FILED IN CS OFFICE: YES

OTHER DOCUMENT FILED WITH CS: RECORD OF SURVEY FILED SEPARATELY

CAP DIAGRAM:

