

CORNER INVESTIGATION REPORT

FS INDEX ID: T-17

CORNER:

GCDB ID: 500240 STATE:

DATE: 6/11/2018

HISTORY OF VISITATIONS:

TOWNSHIP: 3S 8W RANGE: 26 & 27 SECTION:

OREGON COUNTY: TILLAMOOK SIUSLAW **FOREST: DISTRICT**: HEBO

(1)1884 - H. MELDRUM, GLO SURVEY (2)1962 - L.M. ROSEBERRY, BLM RESURVEY, RW1/497 & 499

☑YES □NO

(3)1969 - H. RUSSELL, CSF# B-598 (4)1985 - L. BISHOP, CSF# B-1193 & B-1195

NFSL PROPERTY BOUNDARY CORNER?: LINE(S) POSTED:

MERIDIAN: WILLAMETTE

NORTH - 1985 NORTH - 2017

SOUTH - 1985 SOUTH - 2017

MAINTAINED: GUARD POST(S): NORTH ~ 4 FT

SOUTH ~ 4 FT

CORNER HISTORY:

- (1) ESTABLISHED CORNER, SET 18"x12"x6" BASALT STONE & 2 BT'S.
- (2) FOUND STONE & 2 BT'S, SET IRON PIPE/BRASS CAP & 2 NEW BT'S.
- (3) FOUND US CADASTRAL PIPE & BRONZE CAP.
- (4) FOUND IRON PIPE/BRASS CAP, ORIGINAL STONE & 2 BT'S. SETS ALUMINUM PIPE/CAP FOR REFERENCE MONUMENT & MARKS 1 NEW BT.

MONUMENT FOUND/SET:

FOUND A 2-1/2" GALVANIZED IRON PIPE WITH A 3-1/4" BRASS CAP, PROJECTING 13 INCHES ABOVE THE GROUND.

RECORD CORNER ACCESSORIES:

NO TRACE FOUND OF A (1)36" FIR, (2)37" BURNED & ROTTED SNAG

AN INDETERMINATE SIZE ROTTED FIR STUMP WITH NO MARKS VISIBLE.

NO TRACE FOUND OF A (2)14" FIR.

A 23" ROTTED FIR STUMP WITH SCRIBE FRAGMENTS VISIBLE.

A 23" FIR WITH A HEALED SINGLE BLAZE.

A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP FOR RM, PROJECTING 6" ABOVE THE GROUND, MARKED AS DESCRIBED IN (4).

REGISTERED PROFESSIONAL LAND SURVEYOR

whom B. DawI

OREGON DECEMBER 3, 2014 JONATHAN B. DREW II 89396

EXPIRES: 12/31/2019 RECORD MEASUREMENTS:

(1.2)S60°E - 39.6 FT

(1.2.4)N35°W - 46.2 FT

(2)N87°E - 63.36 FT

(2)S85°W - 29.04 FT, (4)29.0 FT

(4)S73°30'W - 44.0 FT

(4)S62°12'15"E - 52.53 FT

NEW CORNER ACCESSORIES:

NO NEW ACCESSORIES ESTABLISHED.

METHOD OF MEASUREMENT:

NO NEW MEASURMENTS TAKEN, FILED AS CONDITION REPORT.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NFSL LINES BEAR: (4)N0°02'18"E - 1168.72 FT & (4)S1°41'53"E - 2551.92 FT

GEODETIC COORDINATES:

LATITUDE: N 45° 16' 51.736"

LONGITUDE: W 123° 38' 47.035"

DOCUMENTS ON FILE AT: WILLAMETTE NATIONAL FOREST 3106 PIERCE PARKWAY, STE D

SPRINGFIELD, OREGON 97477 ELLIPSOID HEIGHT:

DATUM: WGS 84

SOURCE: USGS QUAD MAP, FOR NAVIGATION TO CORNER.

DATE OF INVESTIGATION: 11/21/2018

REPORT BY: JONATHAN B. DREW II, PLS #89396, CFedS #1664

FIELD CREW: JACOB HUNT, USFS SURVEY TECH

CAP DIAGRAM: OF INT TO

WEUL 01 T3S R8W 1/4 S27 S26 ON STRAL MANAGEN

THIS DOCUMENT FILED IN CS OFFICE: YES

OTHER DOCUMENT FILED WITH CS: RECORD OF SURVEY FILED SEPARATELY