

CORNER INVESTIGATION REPORT

FS INDEX ID: U-21

CORNER: SOUTH 1/16 GCDB ID: 600220

DATE: 6/11/2018

HISTORY OF VISITATIONS:

(1)???? - UNKNOWN SURVEYOR & YEAR (2)1985 - L. BISHOP, CSF# B-1196 & B-1195 (3)2013 - T. JONES, CSF# B-3588

TOWNSHIP: 3S 8W STATE:

OREGON

25 & 26 SECTION:

COUNTY: TILLAMOOK FOREST: SIUSLAW

MERIDIAN: WILLAMETTE

DISTRICT: HEBO

NFSL PROPERTY BOUNDARY CORNER?:

☑YES □NO

LINE(S) POSTED:

SOUTH - 2017

NORTH - 1985

MAINTAINED:

RANGE:

NORTH - NONE

GUARD POST(S): NORTH - 3 FT

CORNER HISTORY:

(1) NO RECORD, SET IRON PIPE MONUMENT.

(2) FOUND IRON PIPE OUT OF POSITON, ESTABLISHED CORNER BY PROPORTION BY SURVEY, SET ALUMINUM PIPE/CAP AT CORNER AND FOR RM.

(3) FOUND ALUMINUM PIPE/CAP & 2 RM'S.

MONUMENT FOUND/SET:

FOUND A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP, 4 INCHES BELOW THE GROUND SURFACE.

RECORD CORNER ACCESSORIES:

A 1" IRON PIPE RM BEARS, N30°27'10"E - 29.41 FT, PROJECTING 5" ABOVE THE GROUND

A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP RM BEARS. N86°07'23"W - 63.52 FT, PROJECTING 6" ABOVE GROUND & MARKED AS DESCRIBED IN (2).

REGISTERED PROFESSIONAL LAND SURVEYOR

ewhem 15.1 OREGON JONATHAN B. DREW II 89396

EXPIRES: 12/31/2019 **RECORD MEASUREMENTS:**

(2)N30°31'E - 29.34 FT (3)N30°30'41"W - 29.40 FT (2)N85°56'W - 64 7 FT (3)N86°09'34"W - 63.67 FT

NEW CORNER ACCESSORIES:

NO NEW ACCESSORIES ESTABLISHED.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT AT SIDE-CENTER, BEARINGS TO CENTER. HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NFSL LINES BEAR: S1°03'56"E - 1263.38 FT & (2)N1°03'56"W - 1263.60 FT

GEODETIC COORDINATES:

DOCUMENTS ON FILE AT:

LATITUDE: N 45° 16' 38.476" LONGITUDE: W 123° 37' 35.351"

WILLAMETTE NATIONAL FOREST 3106 PIERCE PARKWAY, STE D SPRINGFIELD, OREGON 97477

ELLIPSOID HEIGHT: DATUM: WGS 84

SOURCE: USGS QUAD MAP, FOR NAVIGATION TO CORNER.


DATE OF INVESTIGATION: 11/21/2017

REPORT BY: JONATHAN B. DREW II, PLS# 89396, CFedS# 1664 FIELD CREW: ANDREW HILLMAN, USFS SURVEY TECH.

JACOB HUNT, USFS SURVEY TECH.

METHOD OF MEASUREMENT: TRAVERSE RUN FROM THIS CORNER TO

THE SECTION CORNER \$25, 26, 35 & 36. HELD RECORD BEARING (6)S01°03'56"E FOR BASIS OF BEARINGS. RETRACED DISTANCE 1263.38 FT RECORD DISTANCE: (6)1263.60 FT BT DISTANCES TO ALUMINUM NAIL SET



THIS DOCUMENT FILED IN CS OFFICE: YES

OTHER DOCUMENT FILED WITH CS: RECORD OF SURVEY FILED SEPARATELY