CORNER INVESTIGATION REPORT

FS INDEX ID: O-23

TOWNSHIP: 3S

RANGE:

CORNER: CENTER NORTH 1/16 GCDB ID: 604360

DATE: 5/2/2018

HISTORY OF VISITATIONS:

OTHER INTERIOR CORNERS

(1)1964 - L. WHITMORE, PER BT TAGS AT

(2)1986 - J. GAHLSDORF, CSF# B-1215

STATE: OREGON
COUNTY: TILLAMOOK
FOREST: SIUSLAW

SECTION: 24 FOREST: SIUSL MERIDIAN: WILLAMETTE DISTRICT: HEBO

NFSL PROPERTY BOUNDARY CORNER?: □YES □NO

LINE(S) POSTED: NORTH - 1986 EAST - 1986 MAINTAINED: NORTH - NONE EAST - NONE GUARD POST(S): EAST - 2.3 FT

CORNER HISTORY:

(1)NO RECORD, SET IRON PIPE & 2 BT'S

(2)FOUND IRON PIPE OUT OF POSITION WITH 2 BT'S PRESENT, ESTABLISHED CORNER BY SURVEY, SET ALUMINUM PIPE/CAP & 2 NEW BT'S.

MONUMENT FOUND/SET:

FOUND A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP, PROJECTING 2" ABOVE THE GROUND.

RECORD CORNER ACCESSORIES:
ALL MEASURMENTS FROM TRUE CORNER.

A 30" FIR BEARS, N42°W - 19.2 FT, WITH A HEALED SINGLE BLAZE.

A27" FIR SNAGE BEARS, S5°30'E - 34.9 FT, WITH A HEALED SINGLE BLAZE.

A 1-1/2" YELLOW PAINTED GALVANIZED IRON PIPE FOR RM BEARS, \$15°41'W - 12.9 FT TO CENTER OF PLUMBERS CAP, PROJECTING 28" ABOVE GROUND & LEANS SLIGHTLY SOUTH. PAINTED PIPE RED.

A 24" HEMLOCK 8 FT TALL HIGH STUMP BEARS, N28°45'E - 10.6 FT, WITH A HEALED SINGLE BLAZE.

A 34" HEMLOCK BEARS, S42°30'E - 25.6 FT, WITH A HEALED SINGLE BLAZE. NEW CORNER ACCESSORIES:

NO NEW ACCESSORIES ESTABLISHED.

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON
DECEMBER 3, 2014
JONATHAN B. DREW II
89396

EXPIRES: 12/31/2019 RECORD MEASUREMENTS:

(1)N18°W - 28.7 FT FROM RM

(1)S15°30'E - 23.0 FT FROM RM

(2)S16°W - 12.9 FT

(2)N30°E - 10.7 FT

(2)S42°E - 26.1 FT METHOD OF MEASUREMENT:

TRIMBLE S7 TOTAL STATION, SEE RECORD OF SURVEY FOR BASIS OF BEARINGS & OTHER INFORMATION.

BT BEARINGS TO CENTER, DISTANCES TO AN ALUMINUM NAIL SET AT SIDE CENTER.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NFSL LINES BEAR: N0°07'28"E - 1288.29 FT & S0°06'49"W - 1288.63 FT

<u>GEODETIC COORDINATES:</u> LATITUDE: N 45° 17' 54.66428" LONGITUDE: W 123° 37' 00.56258" DOCUMENTS ON FILE AT:

WILLAMETTE NATIONAL FOREST 3106 PIERCE PARKWAY, STE D SPRINGFIELD, OREGON 97477

ELLIPSOID HEIGHT: ~1802 FT DATUM: NAD83(2011), EPOCH:2010.0000

SOURCE: CONSTRAINED LEAST SQUARES NETWORK ADJUSTMENT, SEE MAP.

DATE OF INVESTIGATION: 1/13/2018

REPORT BY: JONATHAN B. DERW II, PLS 89396, CFedS#1664

FIELD CREW: JONATHAN B. DREW II, PLS#89396, CFedS# 1664

MICHAEL HUCK, BLM SURVEY TECH

1986 1986 1986 1986

THIS DOCUMENT FILED IN CS OFFICE: YES

OTHER DOCUMENT FILED WITH CS: RECORD OF SURVEY

