CORNER INVESTIGATION REPORT

FS INDEX ID: N-21

SECTION CORNER:

GCDB ID: 600400

DATE: 5/11/2018

TOWNSHIP: 3S RANGE:

10W

STATE: COUNTY: TILLAMOOK

OREGON

13, 14, 23 & 24 SECTION: MERIDIAN: WILLAMETTE FOREST: SIUSLAW

NFSL PROPERTY BOUNDARY CORNER?:

DISTRICT: HEBO

✓YES □NO WEST - 1982 SOUTH - 1979

LINE(S) POSTED: MAINTAINED:

NORTH - 1982 NORTH - 2017 EAST - 1979 EAST - 2017

SOUTH - NONE WEST - NONE

NORTH - 6 FT SOUTH - 4 FT

GUARD POST(S): EAST - 2.5 FT CORNER HISTORY:

(1) ESTABLISHED CORNER, SET POST & 4 BT'S.

(2) SET 3/4" PIPE & 4 BT'S, NO MENTION OF EXISTING EVIDENCE FOUND. (3) FOUND 3/4" IRON PIPE WITH BT'S.

(4) FOUND 3/4" IRON PIPE WITH 4 BT'S, SETS ALUMINUM PIPE/CAP & 1 NEW BT.

(5) FOUND ALUMINUM PIPE/CAP & 8 BT'S, MARKS 1 NEW BT.

MONUMENT FOUND/SET:

FOUND A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP PROJECTING 10" ABOVE THE GROUND.

RECORD CORNER ACCESSORIES:

A ROTTEN FIR STUMP, SIZE INDETERMINNAT WITH NO MARKS VISIBLE. A ROTTEN FIR STUMP, SIZE INDETERMINANT WITH NO MARKS VISIBLE. A ROTTEN FIR STUMP, SIZE INDETERMINANT WITH A HEALED SINGLE BLAZE.

NO TRACE FOUND OF A (1)3 1/2" FIR. AN INDETERMINANT SIZE ROTTEN FIR STUMP WITH NO MARKS VISIBLE.

A 55" FIR WITH A HEALED SINGLE BLAZE.

NO TRACE FOUND OF A (2)16" ALDER. NO TRACE FOUND OF A (2)22" ALDER.

A 23" FIR WITH A HEALED SINGLE BLAZE.

A 33" FIR WITH A HEALED SINGLE BLAZE.

(4)1979 - L.D. BISHOP, CSF# B-831 (5)1982 - E.R. COOK & D.K. BATEMAN,

(1)1882 - W.P. WRIGHT - GLO SURVEY

(3)1970 - R.A. MORRIS, CSF# A-2020

(2)1959 - M. WHITMORE, RW Bk.2 Pg.409

HISTORY OF VISITATIONS:

& B-841

REGISTERED **PROFESSIONAL** LAND SURVEYOR

Than B. Dew I OREGON JONATHAN B. DREW II

89396 EXPIRES: 12/31/2019 **RECORD MEASUREMENTS:**

(1,5)S20°E - 42.9 FT

(1)N87°W - 14.52 FT, (5)TO FACE

(1)N40°E - 49.5 FT, (5)45.4 FT (1)S16°W - 79.2 FT

(2)N51°30'E - 74.0 FT, (5)SLOPE, (4)61.9 FT

(2,4)S50°30'W - 27.0 FT, (5)S48°W

(2)S28°E - 36.0 FT, (4)32.7 FT, (5)34.8 FT

(2,4)N33°W - 16.0 FT

(4,5)N69°W - 9.8 FT

(5)N88°E - 47.3 FT

NEW CORNER ACCESSORIES:

NO NEW ACCESSORIES ESTABLISHED.

METHOD OF MEASUREMENT:

NO NEW MEASUREMENTS TAKEN.

FILED AS CONDITION REPORT.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NFSL LINES BEAR: (5)N88°01'22"W - 2699.43 FT, (5)N0°06'36"W - 1312.01 FT

GEODETIC COORDINATES: LATITUDE: N 45° 18' 09.074" **DOCUMENTS ON FILE AT:**

LONGITUDE: W 123° 51' 49.089"

WILLAMETTE NATIONAL FOREST 3106 PIERCE PARKWAY, STE D SPRINGFIELD, OREGON 97477

ELLIPSOID HEIGHT:

DATUM: WGS 84

SOURCE: USGS QUAD MAP, FOR NAVIGATION TO CORNER.

DATE OF INVESTIGATION: 12/06/2017

REPORT BY: JONATHAN B. DREW II, PLS#89396, CFedS#1664

FIELD CREW: JACOB HUNT, USFS SURVEY TECH

KYRK BARRON, USFS FIRE F.E.O.

CAP DIAGRAM: SERVICE FOREST 8.00 b. R10W T 3 S 5 S14 \$13 823 \$22 1979 PLS 896
PLS 896
PLS 896

THIS DOCUMENT FILED IN CS OFFICE: YES OTHER DOCUMENT FILED WITH CS: NONE

