## CORNER INVESTIGATION REPORT

FS INDEX ID: Z-1 & A-1

CORNER: SECTION CCC

GCDB ID: 100100 & 100700 DATE: 12/2/2019

TOWNSHIP: 3S & 4S

STATE:

8W RANGE:

**OREGON** COUNTY: TILLAMOOK

SECTION:

FOREST:

SIUSLAW

MERIDIAN: WILLAMETTE

**DISTRICT:** HEBO

31 & 6

NFSL PROPERTY BOUNDARY CORNER?: ☑YES □NO LINE(S) POSTED: NORTH - NONE EAST - 2018

MAINTAINED:

GUARD POST(S): NORTH - 1.5 FT EAST - 3.0 FT

CORNER HISTORY:

(1) ESTABLISHED CORNER BY SURVEY, SET ALUMINNUM PIPE/CAP & 2 BT'S.

(2) FOUND & TIED CORNER MONUMENT.

MONUMENT FOUND/SET:

FOUND A 2-1/2" ALUMINUM PIPE WITH A 3-1/4" ALUMINUM CAP, PROJECTING 2 INCHES ABOVE THE GROUND.

RECORD CORNER ACCESSORIES:

NO TRACE FOUND OF A (1)15" ALDER

NO TRACE FOUND OF A (1)19" ALDER

**NEW CORNER ACCESSORIES:** 

A 15" FIR BEARS, S61°30'E - 17.8 FT, MARKED "CCCS6""BT" ON A DOUBLE BLAZE.

A 19" FIR BEARS, N49°45'E - 5.1 FT, MARKED "CCCS31""BT" ON A DOUBLE BLAZE.

A 2-1/4" GALVANIZED IRON PIPE WITH A 2-1/2" BRASS CAP BEARS, S89°23'09"W -48.01 FT, PROJECTING 15 INCHES ABOVE THE GROUND, FOR SOUTHEAST CORNER OF SECTION 36. (1)S89°19'18"W - 47.93 FT

NEW BT'S INCLUDE A 3/4" BRASS WASHER NAILED BETWEEN "B"&"T" SCRIBES.

CORNER MAINTENANCE/OTHER INFO:

CLEAR BRUSH FROM AROUND MONUMENT & TO BT'S, BT FACES & A 6" BAND AT HEAD HEIGHT PAINTED RED. ADD NEW NAILS TO BT TAGS & ADD NEW TAGS WHERE NEEDED. MONUMENT SIZES ARE OUTSIDE DIAMETER & BT DIAMETERS ARE AT BREAST HEIGHT.

NOTE: THIS RECORD WAS ORIGINALLY SUBMITTED IN OCTOBER 2018, THE REDLINE CORRECTIONS WERE INADVERTANTLY MISPLACED UNTIL THIS DATE.

NFSL LINES BEAR: (1)N89°19'18"E - 514.66 FT & (1)N0°22'39"W - 215.81 FT NOTE: MEASURED DISTANCE CCC S31/S6 TO W1/16 S31/S6 IS 514.80 FT

GEODETIC COORDINATES:

DOCUMENTS ON FILE AT:

LATITUDE: N 45° 15' 29.857" LONGITUDE: W 123° 43' 24.558" WILLAMETTE NATIONAL FOREST 3106 PIERCE PARKWAY, STE D SPRINGFIELD, OREGON 97477

ELLIPSOID HEIGHT:

DATUM: WGS84

SOURCE: CONSUMER GRADE GPS, FOR NAVIGATION TO CORNER.

DATE OF INVESTIGATION: 1/8/2018

REPORT BY: JONATHAN B. DREW II, PLS# 89396

ASSISTED BY: JONATHAN B. DREW II, PLS# 89396

WAVERLY K. HAYNER, BLM SURVEY TECH MICHAEL E. HUCK, BLM SURVEY TECH LOWELL PEARSON, BLM SURVEY TECH

**HISTORY OF VISITATIONS:** 

(1) 1984 - J.W. PROCHNAU CSF# B-1173, B-1175 & B-1176

> REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON JONATHAN B. DREW II 89396

uthor B. DresTI

EXPIRES: 6/30/2021 RECORD MEASUREMENTS:

(1)S61°E - 26.6 FT

(1)N88°E - 49.4 FT

METHOD OF MEASUREMENT: TRIMBLE S7 TOTAL STATION, OPEN TRAVERSE BETWEEN THIS CORNER &

THE WEST 1/16 CORNER FOR SECTION 6, T4S, AND SECTION 31, T3S, HOLD RECORD BEARING, (1)N89°19'18"E, BETWEEN CORNERS FOR BASIS. BEARINGS TO CENTER, DISTANCE TO

ALUMINUM NAIL AT SIDE CENTER.

COREST T 3 8 R B W Seb 9 8 8 9

THIS DOCUMENT FILED IN CS OFFICE: YES OTHER DOCUMENT FILED WITH CS: NONE

