| Dex File No. T. 5 | S 9W M. Tract or Surv. No. Sec. 129128 |
|-------------------------------|--|
| Index R-9 | CORNER RECORD (SEARCH) Tract or Cor. Survey No |
| † <u>5</u> S R. <u>9</u> W | R.D. Hebo County Tillamook 77 83 |
| Merid. Willamette | N.F. Siuslaw Stote Oregon UU |
| CORNER DIAGRAM | DESCRIBE CORNER MONUMENT FOUND |
| T5S R9W | 3/4" pipe 30" above ground. Old wooden post 12" long in rock mound with scribing visible |
| 20 <u>21</u> 29 23 | |
| | DESCRIBE BEARING TREES OR OTHER OFFICIAL ACCESSORIES FOUND A fir 14 brs N412E 10.7 ft; scribing visible |
| · • • | An alder 15" brs S42½E 19.0 ft; bark scribed An alder 15" brs S29W 35.5 ft; bark scribed A fir 20" brs N31W 9.0 ft; scribing visible |
| PHOTO IDENTIFICATION DATA | 1887 BT's in their proper location but scribing rott off |
| Object Ident | DESCRIBE CORNER LOCATION RELATIVE TO NEAR-BY FEATURES, ALSO HOW TO REACH CORNER |
| Ident. By | Go to white section line post on Rt 22 approximately |
| Signature | |
| PLANE COORDINATE POSITION DAT | west on the break of a bench to a steep south |
| State Zone | racing slope in mixed fir and alder timber. |
| Signature Culler | Title Division eadquarters Date 7100-5. 6RLS 650 1969 REV. 65 |

CORNER RECORD (PE _____TUATION) NT DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT et a 2" x 30" iron pipe with brass cap marked T 5 S et 3/4" pipe and old post along side the corner 1969 iled stone back around pipe 650 RIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE et, a 6' steel post north of the corner with a F.S. boundary sign et a 6' steel post west of corner with F.S. boundary sign facing laced BT tags on all BT's and painted red band around all BT's urveyor Date 9/29/6 State Registration Narls 650 ne ByT. C. McCullough Title Cor. Record Prepared ? Yes - No Courthouse, itnesses to the above corner: Richard L. Bryant Michael D. Wilson