

	Corner Visits		
Monument/Accessory *	Location from Corner	Witnesses	Date
At the SE 1/16 corner betw I place a 1" galv. iron pip marked"T2NR7WS9S1/16S101955 A 46" Hemlock mkd. "S101/15 A 10" Hemlock mkd. "S91/163	e 30" long 20" in the grou LS322" from which: BT" N18 E 16.2ft.	B. Mason Jr.	12/22/56
	•		ļ
		• •	
5			
			
S. Carrier	•		

		CORNER VISITS					
	MGHUFFENT/ACCESSORY*	LOCATION FROM CORNER	WI	TNESS	ZS·	DATE]
	blazed tree agreeing in age blaze with the original no chopped away. From this to S34 E which falls in the re point show that the souther	tes. The marks have been ee, I set a point 27 feet a ad. Measurements from this ly BT's have been graded ou	t t	Mason	Jr.	12/5/56	
	the calls to the south and measurements also check mes of 1891, but they do not cluster the true corner falls	in the travelled way. T se	he Lat			, "	
100	a witness corner 55.1ft. So set an unmarked 12" galv. i ground from which: "A 42" Hemlock stump mkd. "WCS16T2NBT".	uth. For the witness corne ron pipe 30" long, 20" in t	L۳			• •	
	A-50" Fir stump mkd. "S17LS322BT" A 39" Fir stump mkd. "WCS81956BT".	S47 W 58.0ft. N62 W 45.3ft.					

*NOTE CONDITION AND ORIGIN

Secs. 8-9-16-1	7″	Sec."	Cor.
T_2N_R_7_	**		ine Info.
[Corner not acco	epted by Surveyor ar post scribed	General	ine Xing
	des ω / 58-59-3 south of 120 road. 7^{E} ft. From corner		Y.T.
	, 26ft, " " wer edge of eatfa	_	cd except
in pointed on 1965 photos	Card by Jaques	Date Corigi	